

## TESLA TC25H3-0922D



### FEATURES

Auto-restart, Self-Cleaning, Child Lock, Anti-rust Cabinet, Easy to clean panel, Washable Filter, Intelligent Defrost, Timer Switch, Self-Diagnosis, Turbo, Independent Dehumidifying, Cold Air Protection, Mold Proof Operation, Sleep Mode, Inner-grooved copper tubes, Multi-folding Evaporator, Vitamin C Filter, Ionizer filter

<b>Capacity</b>			9000BTU	
<b>Energy rate</b>			D/D	
<b>Rated volt and frequency</b>		Ph-V-Hz	220-240/50	
<b>Cooling</b>	Cooling capacity	W	2500	
	Cooling power input	W	920	
	Cooling current input	A	4,2	
	EER	w/w	2,72	
<b>Heating</b>	Heating capacity	W	2500	
	Heating power input	W	880	
	Heating current input	A	4	
	COP	w/w	2,84	
<b>Max. input consumption</b>		W	1500	
<b>Max. current</b>		A	7,0	
<b>Compressor</b>	Model No.		PH160G1C-4DZDE1	
	Type (Rotary/Piston/scroll)		Rotary	
	Brand		GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YDK-14-4 (030020115)	
		Power input	W	40
		Capacity	uF	1,2
		Indoor Fan Speed RPM	r/min	1350
	Indoor Air Circulation		m3/h	450
	Indoor Noise Level dB		dB(A)	29~38
	Net Dimension (LxWxH)		mm	745x250x195
	Packing Dimension (LxWxH)		mm	835x330x278
	Net Weight/Gross Weight		Kg	9/11
	<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK-30-6E
Power input			W	75
Capacity			uF	2
Outdoor Fan Speed RPM			r/min	870
Outdoor Noise Level dB		dB(A)	51	
Net Dimension (LxWxH)		mm	680x225x482	
Packing Dimension(LxWxH)		mm	812x329x535	
Net Weight/Gross Weight		Kg	24/28	
Refrigerant type/weight		g	R22/600	
Design pressure (Hi/Low)		MPa	2.47/0.7	
<b>Refrigerant piping</b>	Liquid side/ Gas side/Length	mm	φ6.0+φ9.52x3500	
	Max. refrigerant pipe length/ Max. difference in level	m	15/5	