

TESLA TC25H3-09410A



FEATURES

Auto-restart, Self-Cleaning, Child Lock, Anti-rust Cabinet, Easy to clean panel, Washable Filter, Intelligent Defrost, Timer Switch, Self-Diagnosis, Turbo, Independent Dehumidifying, Cold Air Protection, Mold Proof Operation, Sleep Mode, Inner-grooved copper tubes, Multi-folding Evaporator, Vitamin C Filter, Ionizer filter

Capacity			9000BTU	
Rated volt and frequency		Ph-V-Hz	220-240V/50Hz	
Cooling	Cooling capacity	W	2700	
	Cooling power input	W	840	
	Cooling current input	A	3,8	
	EER	w/w	3,21	
	Energy Class		A	
Heating	Heating capacity	W	2750	
	Heating power input	W	760	
	Heating current input	A	3,5	
	COP	w/w	3,62	
	Energy Class		A	
Max. input consumption		W	1150	
Max. current		A	5,8	
Compressor	Model No.		44A203BK&FJKC	
	Type (Rotary/Piston/scroll)		Rotary	
	Brand		Rechi	
Indoor	Fan motor	Model	YDK-14-4 (TB-SDJ-A07Bc)	
		Power input	W	40
		capacity	uF	1.2
		Indoor Fan Speed RPM	r/min	1350
	Indoor fan	dia.xlength	mm	φ97 × 583
	Indoor Air Circulation		m3/h	500
	Indoor Noise Level dB		dB(A)	30-39
	Net Dimension (L×W×H)		mm	745×250×195
	Packing Dimension (L×W×H)		mm	835×330×278
	Net Weight/Gross Weight		Kg	9/11
Outdoor	Fan motor	Model	YDK-30-6 (030020201R)	
		Power input	W	60
		Capacity	uF	2
		Outdoor Fan Speed RPM	r/min	930/890/880
	Outdoor fan	dia.xheight	mm	φ384 × 136
	Outdoor Noise Level dB		dB(A)	51
	Net Dimension (L×W×H)		mm	700×225×500
	Packing Dimension(L×W×H)		mm	825×320×550
	Net Weight/Gross Weight		Kg	25/29
	Refrigerant type/weight		g	R410A/600
Design pressure (Hi/Low)		MPa	4.2/1.2	
Refrigerant piping	Liquid side/ Gas side/Length	mm	φ6.0 × φ9.52 × 3500	
	Max. refrigerant pipe length/ Max. difference in level	m	15/5	