

## TESLA TC25H3-09410C



### FEATURES

Auto-restart, Self-Cleaning, Child Lock, Anti-rust Cabinet, Easy to clean panel, Washable Filter, Intelligent Defrost, Timer Switch, Self-Diagnosis, Turbo, Independent Dehumidifying, Cold Air Protection, Mold Proof Operation, Sleep Mode, Inner-grooved copper tubes, Multi-folding Evaporator, Vitamin C Filter, Ionizer filter

<b>Capacity</b>			9000BTU	
<b>Rated volt and frequency</b>		Ph-V-Hz	220-240V/50Hz	
<b>Cooling</b>	Cooling capacity	W	2500	
	Cooling power input	W	840	
	Cooling current input	A	3.8	
	EER	w/w	2,98	
	Energy Class		C	
<b>Heating</b>	Heating capacity	W	2500	
	Heating power input	W	760	
	Heating current input	A	3.5	
	COP	w/w	3,29	
	Energy Class		C	
<b>Max. input consumption</b>		W	1150	
<b>Max. current</b>		A	6.1	
<b>Compressor</b>	Model No.		ASN89V1UDZ	
	Type (Rotary/Piston/scroll)		Rotary	
	Brand		GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YDK-14-4	
		Power input	W	40
		capacity	uF	1.2
		Indoor Fan Speed RPM	r/min	1320
	Indoor fan	dia.xlength	mm	φ97×583
	Indoor Air Circulation		m3/h	500
	Indoor Noise Level dB		dB(A)	32-40
	Net Dimension (L×W×H)		mm	745×250×195
	Packing Dimension (L×W×H)		mm	835×330×278
	Net Weight/Gross Weight		Kg	9/11
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK-AI-30-6AH	
		Power input	W	30
		Capacity	uF	1.5
		Outdoor Fan Speed RPM	r/min	950
	Outdoor fan	dia.xheight	mm	φ319×138
	Outdoor Noise Level dB		dB(A)	50
	Net Dimension (L×W×H)		mm	670×250×430
	Packing Dimension(L×W×H)		mm	810×360×475
	Net Weight/Gross Weight		Kg	21/25
	Refrigerant type/weight		g	R410A/570g
Design pressure (Hi/Low)		MPa	4.2/1.2	
<b>Refrigerant piping</b>	Liquid side/ Gas side/Length	mm	φ6.0 + φ9.52×3500	
	Max. refrigerant pipe length/ Max. difference in level	m	15/5	