

## TESLA TC32H3-1222D



### FEATURES

Auto-restart, Self-Cleaning, Child Lock, Anti-rust Cabinet, Easy to clean panel, Washable Filter, Intelligent Defrost, Timer Switch, Self-Diagnosis, Turbo, Independent Dehumidifying, Cold Air Protection, Mold Proof Operation, Sleep Mode, Inner-grooved copper tubes, Multi-folding Evaporator, Vitamin C Filter, Ionizer filter

<b>Capacity</b>			12000BTU	
<b>Energy rate</b>			D/D	
<b>Rated volt and frequency</b>		Ph-V-Hz	220-240/50	
<b>Cooling</b>	Cooling capacity	W	3000	
	Cooling power input	W	1120	
	Cooling current input	A	5,0	
	EER	w/w	2,68	
<b>Heating</b>	Heating capacity	W	3200	
	Heating power input	W	1100	
	Heating current input	A	4,9	
	COP	w/w	2,91	
<b>Max. input consumption</b>		W	1450	
<b>Max. current</b>		A	8,0	
<b>Compressor</b>	Model No.		PH200M1A-4DZ1	
	Type (Rotary/Piston/scroll)		Rotary	
	Brand		GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YDK-14-4 (030020115)	
		Power input	W	40
		Capacity	uF	1.2
		Indoor Fan Speed RPM	r/min	1350
	Indoor Air Circulation	m3/h	600	
	Indoor Noise Level dB	dB(A)	31-42	
	Net Dimension (LxWxH)	mm	745x250x195	
	Packing Dimension (LxWxH)	mm	833x330x278	
	Net Weight/Gross Weight	Kg	9/11	
	<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK-35-6A H (320222005)
Power input			W	67
Capacity			uF	2
Outdoor Fan Speed RPM			r/min	900
Outdoor Noise Level dB		dB(A)	54	
Net Dimension (LxWxH)		mm	715x235x540	
Packing Dimension(LxWxH)		mm	851x335x600	
Net Weight/Gross Weight		Kg	28/33	
Refrigerant type/weight		g	R22/680g	
Design pressure (Hi/Low)		MPa	2.45/0.7	
<b>Refrigerant piping</b>	Liquid side/ Gas side/Length	mm	φ6.0+φ9.52x3500	
	Max. refrigerant pipe length/ Max. difference in level	m	15/5	