

## TESLA TC32H3-12410A



### FEATURES

Auto-restart, Self-Cleaning, Child Lock, Anti-rust Cabinet, Easy to clean panel, Washable Filter, Intelligent Defrost, Timer Switch, Self-Diagnosis, Turbo, Independent Dehumidifying, Cold Air Protection, Mold Proof Operation, Sleep Mode, Inner-grooved copper tubes, Multi-folding Evaporator, Vitamin C Filter, Ionizer filter

<b>Capacity</b>			12000BTU	
<b>Rated volt and frequency</b>		Ph-V-Hz	220-240V/50Hz	
<b>Cooling</b>	Cooling capacity	W	3200	
	Cooling power input	W	995	
	Cooling current input	A	4,5	
	EER	w/w	3,22	
	Energy Class		A	
<b>Heating</b>	Heating capacity	W	3550	
	Heating power input	W	983	
	Heating current input	A	4,30	
	COP	w/w	3,61	
	Energy Class		A	
<b>Max. input consumption</b>		W	1500	
<b>Max. current</b>		A	6,5	
<b>Compressor</b>	Model No.		ASM135V1VDZ	
	Type (Rotary/Piston/scroll)		Rotary	
	Brand		GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YDK-14-4 (030020115R)	
		Power input	W	40
		capacity	uF	1.2
		Indoor Fan Speed RPM	r/min	1350
	Indoor fan	dia.xlength	mm	φ97×583
	Indoor Air Circulation		m3/h	500
	Indoor Noise Level dB		dB(A)	32-40
	Net Dimension (L×W×H)		mm	745×250×195
	Packing Dimension (L×W×H)		mm	833×330×278
	Net Weight/Gross Weight		Kg	9/11
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK-35-6A H (320222005R)	
		Power input	W	67
		Capacity	uF	2
		Outdoor Fan Speed RPM	r/min	900
	Outdoor fan	dia.xheight	mm	φ408×134
	Outdoor Noise Level dB		dB(A)	54
	Net Dimension (L×W×H)		mm	715×235×540
	Packing Dimension(L×W×H)		mm	851×335×600
	Net Weight/Gross Weight		Kg	28/33
	Refrigerant type/weight		g	R410A/730g
Design pressure (Hi/Low)		MPa	3.8/1.2	
<b>Refrigerant piping</b>	Liquid side/ Gas side/Length	mm	φ6.35+φ9.52×3500	
	Max. refrigerant pipe length/ Max. difference in level	m	15/5	