

## TESLA TC61H3-24410A



### FEATURES

Auto-restart, Self-Cleaning, Child Lock, Anti-rust Cabinet, Easy to clean panel, Washable Filter, Intelligent Defrost, Timer Switch, Self-Diagnosis, Turbo, Independent Dehumidifying, Cold Air Protection, Mold Proof Operation, Sleep Mode, Inner-grooved copper tubes, Multi-folding Evaporator, Vitamin C Filter, Ionizer filter

<b>Capacity</b>			24000BTU	
<b>Rated volt and frequency</b>		Ph-V-Hz	220-240V/50Hz	
<b>Cooling</b>	Cooling capacity	W	6400	
	Cooling power input	W	1990	
	Cooling current input	A	8.9	
	EER	w/w	3,22	
	Energy Class		A	
<b>Heating</b>	Heating capacity	W	6600	
	Heating power input	W	1828	
	Heating current input	A	8.7	
	COP	w/w	3,61	
	Energy Class		A	
<b>Max. input consumption</b>		W	2700	
<b>Max. current</b>		A	14.3	
<b>Compressor</b>	Model No.		PA240X2CS-4KU1	
	Type (Rotary/Piston/scroll)		Rotary	
	Brand		GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YDK-27-4 A6 (320202023)	
		Power input	W	56
		capacity	uF	1,8
		Indoor Fan Speed RPM	r/min	1300/1150/1000
	Indoor fan	dia.xlength	mm	φ102×707
	Indoor Air Circulation		m3/h	900
	Indoor Noise Level dB		dB(A)	42-46
	Net Dimension (L×W×H)		mm	900×292×215
	Packing Dimension (L×W×H)		mm	983×377×300
	Net Weight/Gross Weight		Kg	14/17
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK-40-6A 1 (320222029)	
		Power input	W	106
		Capacity	uF	3
		Outdoor Fan Speed RPM	r/min	870
	Outdoor fan	dia.xheight	mm	φ415
	Outdoor Noise Level dB		dB(A)	54
	Net Dimension (L×W×H)		mm	850×295×605
	Packing Dimension(L×W×H)		mm	995×415×690
	Net Weight/Gross Weight		Kg	45/51
	Refrigerant type/weight		g	R410A/1900
Design pressure (Hi/Low)		MPa	4.0-1.2	
<b>Refrigerant piping</b>	Liquid side/ Gas side/Length	mm	φ6.0 + φ12.7×4000	
	Max. refrigerant pipe length/ Max. difference in level	m	15/5	