

## TESLA TC32H3-12410IA



### SPECIFICATIONS

#### Inverter Split Type A Models

<b>Capacity</b>		12000BTU	
<b>Rated volt and frequency (Ph-V-Hz)</b>		1-220-240/50	
<b>Mode</b>		<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity (W)</b>		3200W (1800W~3500W)      2800W (1600W~3400W)	
<b>Power input (W)</b>		1080W (450W~1300W)      760W (350W~1100W)	
<b>Current input (A)</b>		4.9A (2.3A~5.7A)              3.5A (1.8A~4.8A)	
<b>Working temperature</b>		-15 to 46                              -15 to 24	
<b>SEER/SCOP (W/W)</b>		5.6/A+                                  3.8/A	
<b>Design load (W)</b>		3200                                      2800	
<b>T biv. (°C) Heating balance point temperature</b>		/    -7	
<b>T ol. (°C) Heating limit operating temperature</b>		/    -10	
<b>Thermostat-off mode (W)</b>		30	
<b>Stand by mode (W)</b>		0,5	
<b>Throttle type</b>		Capillary	
<b>Annual consumption (KW)</b>		200    1032	
<b>(L/h) Moisture Removal</b>		1,2	
<b>Compressor</b>	Model	ASK89D53UEZ	
	Type (Rotary, Piston, scroll)	Rotary	
	Brand	GMCC	
	Capacity (W)	2645	
	Power input (W)	682	
<b>Indoor</b>	<b>Fan motor</b>	Model	YDK-16-4 9
		Power type	AC
		Power input (W)	16
		Capacitance (uF)	1
		Indoor Fan Speed RPM (High/Med/Low)	1250/1100/850
	Indoor fan	dia. x length (mm)	φ92×593
	Indoor Air Circulation (m3/h)	550	
	Dimension (LxWxH) (mm)	780×276×202	
	Packing (LxWxH) (mm)	960×367×305	
	Net/Gross weight (Kg)	10/12	
Noise sound pressure level (dB/A)	30~39		
Sound power noise (dB/A)	40~49w		
<b>Outdoor</b>	<b>Fan motor</b>	Model	D-280-25-8H
		Power type	DC
		Power input (W)	25
		Indoor Fan Speed RPM (High/Med/Low)	1150
	Outdoor fan	dia. x length (mm)	φ408×134
	Dimension (LxWxH) (mm)	715×235×540	
	Packing (LxWxH) (mm)	851×335×600	
	Net/Gross weight (Kg)	27/29	
	Noise sound pressure level (dB/A)	53	
	Sound power noise (dB/A)	63	
Refrigerant type/weight	R410A/780		