

## TESLA TA36FFLL-1232IA



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi option, I FEEL function

<b>Capacity</b>			12000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>		W	3200(1400-3520)      3500(1100-3750)
<b>Power input</b>		W	997(450-1500)      970(400-1350)
<b>Current input</b>		A	4.33(2.0-7.5)      4.3(1.6-7.0)
<b>SEER-SCOP/ Energy Class</b>		W/W	6.17/A++      4.06/A+
<b>Operating range (°C)</b>			14 - 43°C      -15 - 30°C
<b>Dehumidifying</b>		Kg/h	1.1
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I
<b>Max. input consumption</b>		W	1800
<b>Max. current</b>		A	8.5
<b>Compressor</b>		Model	ASK103D53UFZE
		Type	DC
		Brand	GMCC
<b>Indoor</b>	<b>Fan motor</b>	Model	YYK18-4B
		Power input	W
		Capacity	uF
		Indoor Fan Speed RPM	r/min
	<b>Indoor fan</b>	Dia. / Length	mm
	<b>Indoor Air Circulation (m³/h)</b>	m³/h	480
	<b>Indoor Noise Level dB</b>	dB(A)	33/29/27/24
	<b>Net Dimension (LxWxH)</b>	mm	700x285x188
	<b>Packing Dimension (LxWxH)</b>	mm	750x355x260
	<b>Net Weight/Gross Weight</b>	Kg	7,8/9,3
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK25-6B
		Power input	W
		Capacity	uF
		Outdoor Fan Speed RPM	r/min
	<b>Outdoor fan</b>	Length	mm
	<b>Outdoor Noise Level dB</b>	dB(A)	52
	<b>Net Dimension (LxWxH)</b>	mm	720x545x255
	<b>Packing Dimension (LxWxH)</b>	mm	835x382x600
	<b>Net Weight/Gross Weight</b>	Kg	27,8/30,4
	<b>Refrigerant type/weight</b>	g	R410A/710
<b>Max. Discharge/Max. Suction pressure</b>	Mpa	4/1	
<b>Refrigerant piping</b>	Liquid side / Gas side	mm	φ6.35(0,5) / φ9.52(0,6)
	Max. refrigerant pipe length / Max. difference in level	m	18/6