

## TESLA TA36FFLL-12410IA



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi option, I FEEL function

<b>Capacity</b>		12000BTU		
<b>Rated volt and frequency</b>		V/Hz		
<b>Mode</b>				
<b>Rated capacity</b>		<b>Cooling</b>	<b>Heating</b>	
<b>Power input</b>		3200(1400-3520)	3500(1100-3750)	
<b>Current input</b>		997(450-1500)	970(400-1350)	
<b>SEER-SCOP/ Energy Class</b>		4.33(2.0-7.5)	4.3(1.6-7.0)	
<b>Operating range (°C)</b>		6.17/A++	4.06/A+	
<b>Dehumidifying</b>		14 - 43°C	-15 - 30°C	
<b>Degree of protection (IN) / (OUT)</b>		Kg/h		
<b>Class of electric protection (IN) / (OUT)</b>		(IP)		
<b>Max. input consumption</b>		IPX4/IPX4		
<b>Max. current</b>		Class I / Class II		
<b>Compressor</b>		I/I		
		W		
		A		
		ASK103D53UFZE		
		DC		
		GMCC		
<b>Indoor</b>	<b>Fan motor</b>	Model		
		Type		
		Brand		
		Model		
	<b>Indoor fan</b>	<b>Power input</b>	W	YYK18-4B
		<b>Capacity</b>	uF	18
		<b>Indoor Fan Speed RPM</b>	r/min	1.5
			1250	
			mm	Ø97.8/558
	<b>Indoor Air Circulation (m³/h)</b>		m³/h	480
<b>Indoor Noise Level dB</b>		dB(A)	33/29/27/24	
<b>Net Dimension (LxWxH)</b>		mm	700x285x188	
<b>Packing Dimension (LxWxH)</b>		mm	750x355x260	
<b>Net Weight/Gross Weight</b>		Kg	7,8/9,3	
<b>Outdoor</b>	<b>Fan motor</b>	Model		
		Type		
		Brand		
		Model		
	<b>Outdoor fan</b>	<b>Power input</b>	W	YDK25-6B
		<b>Capacity</b>	uF	25
		<b>Outdoor Fan Speed RPM</b>	r/min	1.5
			820	
			mm	390
	<b>Outdoor Noise Level dB</b>		dB(A)	52
<b>Net Dimension (LxWxH)</b>		mm	720x545x255	
<b>Packing Dimension (LxWxH)</b>		mm	835x382x600	
<b>Net Weight/Gross Weight</b>		Kg	27,8/30,4	
<b>Refrigerant type/weight</b>		g	R410A/710	
<b>Max. Discharge/Max. Suction pressure</b>		Mpa	4/1	
<b>Refrigerant piping</b>	<b>Liquid side / Gas side</b>		mm	
	<b>Max. refrigerant pipe length / Max. difference in level</b>		m	
		Ø6.35(0,5) / Ø9.52(0,6)		
		18/6		