

TESLA TA53FFLL-18410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer, I FEEL function

Capacity			18000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	5300 5450	
Power input		W	1656 1509	
Current input		A	7.2 6.56	
EER-COP		W/W	3.21 3.61	
Energy Class			A A	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2200	
Max. current		A	11.1	
Compressor		Model	ASL185CV-C7LQ	
		Type (Rotary/Piston/scroll)	ROTARY	
		Brand	HIGHLY	
Indoor	Fan motor	Model	YYK25-4D	
		Power input	W	25
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	1230
	Indoor fan	Dia. / Length	mm	Ø107.9 / 661
	Indoor Air Circulation (m³/h)		m³/h	850
	Indoor Noise Level dB		dB(A)	38/35/32/29
	Net Dimension (LxWxH)		mm	850x300x198
Packing Dimension (LxWxH)		mm	885x355x255	
Net Weight/Gross Weight		Kg	11/13,3	
Outdoor	Fan motor	Model	YDK31-6A	
		Power input	W	31
		Capacity	uF	2.5
		Outdoor Fan Speed RPM	r/min	900
	Outdoor fan	Dia. / Length	mm	Ø421 / 117
	Outdoor Noise Level dB		dB(A)	54
	Net Dimension (LxWxH)		mm	795x525x290
	Packing Dimension (LxWxH)		mm	920x400x620
	Net Weight/Gross Weight		Kg	35/38,7
	Refrigerant type/weight		g	R410/1150
Design pressure (Hi/Low)		Mpa	4.15/1.15	
Refrigerant piping		Liquid side / Gas side	mm	ø6.35(0,5) / ø12.7(0,7)
		Max. refrigerant pipe length / Max. difference in level	m	18/6