

TESLA TA53LLML-1832IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi included, I FEEL function

Capacity			18000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	5300(1200~5500) 5600(1200~5900)	
Power input		W	1650 980	
Current input		A	7.31 6.65	
SEER-SCOP/ Energy Class		W/W	6.55/A++ 4.07/A+	
Operating range (°C)			14 - 43°C -15 - 30°C	
Dehumidifying		Kg/h	1.5	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2900	
Max. current		A	12	
Compressor		Model	KSM135D23UFZ	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	D-310-30-8	
		Power input	W	30
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1180
	Indoor fan	Dia. / Length	mm	Ø106/715
		Indoor Air Circulation (m³/h)	m³/h	900
	Indoor Noise Level dB		dB(A)	57
	Net Dimension (LxWxH)		mm	970x315x235
	Packing Dimension (LxWxH)		mm	1025x385x305
Net Weight/Gross Weight		Kg	12.5/15.5	
Outdoor	Fan motor	Model	D-40-8	
		Power input	W	40
		Capacity	uF	1.5
		Outdoor Fan Speed RPM	r/min	900
	Outdoor fan	Length	mm	421
	Outdoor Noise Level dB		dB(A)	63
	Net Dimension (LxWxH)		mm	800x545x315
	Packing Dimension (LxWxH)		mm	920x400x620
	Net Weight/Gross Weight		Kg	35/38.5
	Refrigerant type/weight		g	R32/1280
Max. Discharge/Max. Suction pressure		Mpa	4,28/1,18	
Refrigerant piping	Liquid side / Gas side	mm	6.35 (1/4) / 12.7 (1/2)	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	