

TESLA TA71LLML-2432IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi included, I FEEL function

Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	7100(1400~7400) 7100(900~7200)	
Power input		W	2200 1960	
Current input		A	9.75 8.67	
SEER-SCOP/ Energy Class		W/W	6.36/A++ 4.32/A+	
Operating range (°C)			14 - 43°C -15 - 30°C	
Dehumidifying		Kg/h	1.7	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	3700	
Max. current		A	16	
Compressor		Model	GTD186UKQA9LT6	
		Type	DC	
		Brand	HIGHLY	
Indoor	Fan motor	Model	YYK50-4	
		Power input	W	
		Capacity	uF	
		Indoor Fan Speed RPM	r/min	
	Indoor fan	Dia. / Length	mm	
			Ø107.9/839	
	Indoor Air Circulation (m³/h)		m³/h	1150
	Indoor Noise Level dB		dB(A)	59
	Net Dimension (LxWxH)		mm	1100x330x235
Packing Dimension (LxWxH)		mm	1160x400x305	
Net Weight/Gross Weight		Kg	15/18	
Outdoor	Fan motor	Model	D-69-8	
		Power input	W	
		Capacity	uF	
		Outdoor Fan Speed RPM	r/min	
	Outdoor fan	Length	mm	
	Outdoor Noise Level dB		dB(A)	65
	Net Dimension (LxWxH)		mm	900x700x350
	Packing Dimension (LxWxH)		mm	1020x430x770
	Net Weight/Gross Weight		Kg	45/49.5
	Refrigerant type/weight		g	R32/1440
Max. Discharge/Max. Suction pressure		Mpa	4,28/1,18	
Refrigerant piping	Liquid side / Gas side	mm	6.35 (1/4)/15.88 (5/8)	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	