

TESLA TA26FFLL-0932IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi included, I FEEL function

Capacity			9000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	2600 (500~2900) 2800(500~3100)	
Power input		W	800 750	
Current input		A	3,56 3,32	
SEER-SCOP/ Energy Class		W/W	6,15/ A++ 4,1/A+	
Operating range (°C)			14 - 43°C -15 - 30°C	
Dehumidifying		Kg/h	1,2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1500	
Max. current		A	8	
Compressor		Model	KSK89D59UFZE	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK12-4B	
		Power input	W	12
		Capacity	uF	1,5
		Indoor Fan Speed RPM	r/min	1150
	Indoor fan	Dia. / Length	mm	ø97.8 / 558
	Indoor Air Circulation (m³/h)		m³/h	560
	Indoor Noise Level dB		dB(A)	51
	Net Dimension (LxWxH)		mm	750x285x200
	Packing Dimension (LxWxH)		mm	800x345x265
	Net Weight/Gross Weight		Kg	8.5/10
Outdoor	Fan motor	Model	D-24-8	
		Power input	W	24
		Capacity	uF	1,5
		Outdoor Fan Speed RPM	r/min	900
	Outdoor fan	Length	mm	390
	Outdoor Noise Level dB		dB(A)	61
	Net Dimension (LxWxH)		mm	730x545x285
	Packing Dimension (LxWxH)		mm	850x370x620
	Net Weight/Gross Weight		Kg	25/27.5
	Refrigerant type/weight		g	R32/530
Max. Discharge/Max. Suction pressure		Mpa	4,28/1,18	
Refrigerant piping	Liquid side / Gas side	mm	6.35 (1/4) / 9,53 (3/8)	
	Max. refrigerant pipe length / Max. difference in level	m	15/10	