

TESLA TA35LLIL-1232IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi included, I FEEL function

Capacity		12000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity		3500(800~3600)	3500(1000~3600)
Power input		1100	980
Current input		4.87	4.32
SEER-SCOP/ Energy Class		6.12/A++	4.07/A+
Operating range (°C)		14 - 43°C	-15 - 30°C
Dehumidifying		Kg/h 1.2	
Degree of protection (IN) / (OUT)		(IP) IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 1900	
Max. current		A 9.5	
Compressor		KSK89D59UFZE	
		DC	
		GMCC	
Indoor	Fan motor	Model YYK14-4	
		Power input W 14	
		Capacity uF 1.5	
		Indoor Fan Speed RPM r/min 1130	
	Indoor fan	Dia. / Length mm Ø92/597	
		Indoor Air Circulation (m³/h) m³/h 580	
	Indoor Noise Level dB dB(A) 51		
	Net Dimension (LxWxH) mm 800x300x199		
	Packing Dimension (LxWxH) mm 900x370x270		
Net Weight/Gross Weight Kg 8.5/10.5			
Outdoor	Fan motor	Model D-24-8	
		Power input W 24	
		Capacity uF 1.5	
		Outdoor Fan Speed RPM r/min 770	
	Outdoor fan	Length mm 390	
	Outdoor Noise Level dB dB(A) 61		
	Net Dimension (LxWxH) mm 730x545x285		
	Packing Dimension (LxWxH) mm 850x370x620		
	Net Weight/Gross Weight Kg 25/27.5		
	Refrigerant type/weight g R32/600		
Max. Discharge/Max. Suction pressure Mpa 4,28/1,18			
Refrigerant piping	Liquid side / Gas side mm 6.35 (1/4)/9,53 (3/8)		
	Max. refrigerant pipe length / Max. difference in level m 15/10		