

## TESLA TA33FFLL-12410A



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer, I FEEL function

<b>Capacity</b>			12000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	3300                              3450	
<b>Power input</b>		W	1028                              955	
<b>Current input</b>		A	4.47                                4.15	
<b>EER-COP</b>		W/W	3.21                                3.61	
<b>Energy Class</b>			A                                      A	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	8.5	
<b>Max. current</b>		A	1750	
<b>Compressor</b>		Model	ASM125V1VFT	
		Type (Rotary/Piston/scroll)	ROTARY	
		Brand	GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YYK18-4B	
		Power input	W	18
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1330
	<b>Indoor fan</b>	Dia. / Length	mm	Ø97.8 / 558
	<b>Indoor Air Circulation (m³/h)</b>		m³/h	560
	<b>Indoor Noise Level dB</b>		dB(A)	36/33/30/27
	<b>Net Dimension (LxWxH)</b>		mm	800x300x197
<b>Packing Dimension (LxWxH)</b>		mm	870x370x282	
<b>Net Weight/Gross Weight</b>		Kg	8/10,8	
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK25-6	
		Power input	W	25
		Capacity	uF	1.5
		Outdoor Fan Speed RPM	r/min	820
	<b>Outdoor fan</b>	Dia. / Length	mm	Ø390 / 140
	<b>Outdoor Noise Level dB</b>		dB(A)	52
	<b>Net Dimension (LxWxH)</b>		mm	660x500x240
	<b>Packing Dimension (LxWxH)</b>		mm	780x570x345
	<b>Net Weight/Gross Weight</b>		Kg	29/31,65
	<b>Refrigerant type/weight</b>		g	R410/660
<b>Design pressure (Hi/Low)</b>		Mpa	4.16/1.17	
<b>Refrigerant piping</b>	<b>Liquid side / Gas side</b>		mm	Ø6.35(0,5) / Ø9.52(0,6)
	<b>Max. refrigerant pipe length / Max. difference in level</b>		m	18/6