

TESLA TA35FFML-12410B



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only)



| | | | | |
|--|--------------------------------------|---|--|-------------------------|
| Capacity | | | 12000BTU | |
| Rated volt and frequency | | V/Hz | 220-240V~/50HZ | |
| Mode | | | Cooling Heating | |
| Rated capacity | | W | 3500 3600 | |
| Power input | | W | 1182 1071 | |
| Current input | | A | 5.14 4.65 | |
| EER-COP | | W/W | 2.96 3.36 | |
| Energy Class | | | B B | |
| Degree of protection (IN) / (OUT) | | (IP) | IPX4/IPX4 | |
| Class of electric protection (IN) / (OUT) | | Class I / Class II | I/I | |
| Max. input consumption | | W | 1550 | |
| Max. current | | A | 7.7 | |
| Compressor | | Model | ASM125V1VDZ | |
| | | Type (Rotary/Piston/scroll) | ROTARY | |
| | | Brand | GMCC | |
| Indoor | Fan motor | Model | YYK18-4B | |
| | | Power input | W | 18 |
| | | Capacity | uF | 1.5 |
| | | Indoor Fan Speed RPM | r/min | 1250 |
| | Indoor fan | Dia. / Length | mm | Ø97.8 / 558 |
| | Indoor Air Circulation (m³/h) | | m³/h | 550 |
| | Indoor Noise Level dB | | dB(A) | 36/33/30/27 |
| | Net Dimension (LxWxH) | | mm | 750x285x200 |
| Packing Dimension (LxWxH) | | mm | 820x347x277 | |
| Net Weight/Gross Weight | | Kg | 8/10.1 | |
| Outdoor | Fan motor | Model | YDK25-6 | |
| | | Power input | W | 25 |
| | | Capacity | uF | 1.5 |
| | | Outdoor Fan Speed RPM | r/min | 820 |
| | Outdoor fan | Dia. / Length | mm | Ø390 / 140 |
| | Outdoor Noise Level dB | | dB(A) | 52 |
| | Net Dimension (LxWxH) | | mm | 710x500x240 |
| | Packing Dimension (LxWxH) | | mm | 780x570x345 |
| Net Weight/Gross Weight | | Kg | 26/29 | |
| Refrigerant type/weight | | g | R410A/610 | |
| Design pressure (Hi/Low) | | Mpa | 4.15/1.15 | |
| Refrigerant piping | | Liquid side / Gas side | mm | Ø6.35(0,5) / Ø9.52(0,6) |
| | | Max. refrigerant pipe length / Max. difference in level | m | 18/6 |