

## TESLA TA35LLML-12410IAW



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi included, I FEEL function

<b>Capacity</b>			12000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	3200(1400-3520)      3500(1100-3750)	
<b>Power input</b>		W	997(450-1500)      970(400-1350)	
<b>Current input</b>		A	4.33(2.0-7.5)      4.3(1.6-7.0)	
<b>SEER-SCOP/ Energy Class</b>		W/W	6.17/A++      4.06/A+	
<b>Operating range (°C)</b>			14 - 43°C      -15 - 30°C	
<b>Dehumidifying</b>		Kg/h	1.1	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	1800	
<b>Max. current</b>		A	8.5	
<b>Compressor</b>		Model	ASK103D53UFZE	
		Type	DC	
		Brand	GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YYK12-4B	
		Power input	W	
		Capacity	uF	
		Indoor Fan Speed RPM	r/min	
	<b>Indoor fan</b>	Dia. / Length	mm	
			Ø92 / 500	
	<b>Indoor Air Circulation (m³/h)</b>		m³/h	480
	<b>Indoor Noise Level dB</b>		dB(A)	33/29/27/24
<b>Net Dimension (LxWxH)</b>		mm	700x285x188	
<b>Packing Dimension (LxWxH)</b>		mm	750x355x260	
<b>Net Weight/Gross Weight</b>		Kg	9/10.5	
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK25-6B	
		Power input	W	
		Capacity	uF	
		Outdoor Fan Speed RPM	r/min	
	<b>Outdoor fan</b>	Length	mm	
	<b>Outdoor Noise Level dB</b>		dB(A)	52
	<b>Net Dimension (LxWxH)</b>		mm	720x545x255
	<b>Packing Dimension (LxWxH)</b>		mm	835x382x600
	<b>Net Weight/Gross Weight</b>		Kg	25/28,4
	<b>Refrigerant type/weight</b>		g	R410A/710
<b>Max. Discharge/Max. Suction pressure</b>		Mpa	4/1	
<b>Refrigerant piping</b>	Liquid side / Gas side	mm	Ø6.35(0,5) / Ø9.52(0,6)	
	Max. refrigerant pipe length / Max. difference in level	m	18/6	