

TESLA TA36FFLL-1232IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi included, I FEEL function

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	3500(1400-3520) 3500(1100-3750)
Power input		W	997(450-1500) 970(400-1350)
Current input		A	4.33(2.0-7.5) 4.3(1.6-7.0)
SEER-SCOP/ Energy Class		W/W	6.17/A++ 4.06/A+
Operating range (°C)			14 - 43°C -15 - 30°C
Dehumidifying		Kg/h	1.1
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1800
Max. current		A	8.5
Compressor		Model	ASK103D53UFZE
		Type	DC
		Brand	GMCC
Indoor	Fan motor	Model	YYK18-4B
		Power input	W
		Capacity	uF
		Indoor Fan Speed RPM	r/min
	Indoor fan	Dia. / Length	mm
	Indoor Air Circulation (m³/h)	m³/h	480
	Indoor Noise Level dB	dB(A)	33/29/27/24
	Net Dimension (LxWxH)	mm	700x285x188
	Packing Dimension (LxWxH)	mm	750x355x260
	Net Weight/Gross Weight	Kg	7,8/9,3
Outdoor	Fan motor	Model	YDK25-6B
		Power input	W
		Capacity	uF
		Outdoor Fan Speed RPM	r/min
	Outdoor fan	Length	mm
	Outdoor Noise Level dB	dB(A)	52
	Net Dimension (LxWxH)	mm	720x545x255
	Packing Dimension (LxWxH)	mm	835x382x600
	Net Weight/Gross Weight	Kg	27,8/30,4
	Refrigerant type/weight	g	R32/600
Max. Discharge/Max. Suction pressure	Mpa	4/1	
Refrigerant piping	Liquid side / Gas side	mm	φ6.35(0,5) / φ9.52(0,6)
	Max. refrigerant pipe length / Max. difference in level	m	18/6