

TESLA TA36FFLL-12410IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi option, I FEEL function

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			CoolingHeating
Rated capacity		W	3200(1400-3520)3500(1100-3750)
Power input		W	997(450-1500)970(400-1350)
Current input		A	4.33(2.0-7.5)4.3(1.6-7.0)
SEER-SCOP/ Energy Class		W/W	6.17/A++4.06/A+
Operating range (°C)			14 - 43°C-15 - 30°C
Dehumidifying		Kg/h	1.1
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1800
Max. current		A	8.5
Compressor		Model	ASK103D53UFZE
		Type	DC
		Brand	GMCC
Indoor	Fan motor	Model	YYK18-4B
		Power input	W18
		Capacity	uF1.5
		Indoor Fan Speed RPM	r/min1250
	Indoor fan	Dia. / Length	mmØ97.8/558
	Indoor Air Circulation (m³/h)		m³/h480
	Indoor Noise Level dB		dB(A)33/29/27/24
	Net Dimension (L×W×H)		mm700×285×188
	Packing Dimension (L×W×H)		mm750×355×260
	Net Weight/Gross Weight		Kg7,8/9,3
Outdoor	Fan motor	Model	YDK25-6B
		Power input	W25
		Capacity	uF1.5
		Outdoor Fan Speed RPM	r/min820
	Outdoor fan	Length	mm390
	Outdoor Noise Level dB		dB(A)52
	Net Dimension (L×W×H)		mm720×545×255
	Packing Dimension (L×W×H)		mm835×382×600
	Net Weight/Gross Weight		Kg27,8/30,4
	Refrigerant type/weight		gR410A/710
Refrigerant piping		Max. Discharge/Max. Suction pressure	Mpa4/1
		Liquid side / Gas side	mmØ6.35(0,5) / Ø9.52(0,6)
		Max. refrigerant pipe length / Max. difference in level	m18/6