

TESLA TA53FFLL-1832IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Wi-Fi included, I FEEL function

Capacity		18000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity		5280 (1200~5400)	5570 (1200~5800)
Power input		1660	1490
Current input		7.35	6.60
SEER-SCOP/ Energy Class		7,1/ A++	4,02/A+
Operating range (°C)		14 - 50°C	-15 - 30°C
Dehumidifying		L/h 1.8	
Degree of protection (IN) / (OUT)		(IP) IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 2900	
Max. current		A 12	
Compressor		Model	KSM135D23UFZ
		Type	DC
		Brand	GMCC
Indoor	Fan motor	Model	D-310-30-8
		Power input	W 30
		Capacity	uF 1,5
		Indoor Fan Speed RPM	r/min 1180
	Indoor fan	Dia. / Length	mm Φ 106x715
	Indoor Air Circulation (m³/h)		m³/h 850
	Indoor Noise Level dB		dB(A) 47
	Net Dimension (LxWxH)		mm 900x315x225
	Packing Dimension (LxWxH)		mm 970x380x295
Net Weight/Gross Weight		Kg 12,0/14	
Outdoor	Fan motor	Model	D-40-8
		Power input	W 40
		Capacity	uF 1,5
		Outdoor Fan Speed RPM	r/min 900
	Outdoor fan	Length	mm 421
	Outdoor Noise Level dB		dB(A) 58
	Net Dimension (LxWxH)		mm 875x355x540
	Packing Dimension (LxWxH)		mm 915x390x595
	Net Weight/Gross Weight		Kg 35,0/37,5
	Refrigerant type/weight		g R32/1280
Max. Discharge/Max. Suction pressure		Mpa 4,28/1,18	
Refrigerant piping	Liquid side / Gas side	mm 6.35 (1/4)/12.7 (1/2)	
	Max. refrigerant pipe length / Max. difference in level	m 30/20	