

TESLA TA53LLML-18410IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WiFi option, I FEEL function

Capacity			18000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	5000 (1800-5200) 5100 (1800-5300)	
Power input		W	1548 (550-2100) 1410 (550-2100)	
Current input		A	6,9 (2,2-10,2) 6,3 (2,2-10,2)	
SEER-SCOP/ Energy Class		W/W	6.48/A++ 4.12/A+	
Operating range (°C)			14 - 43°C -15 - 30°C	
Dehumidifying		Kg/h	1.6	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2200	
Max. current		A	10	
Compressor		Model	ASM135D23UFZ	
		Type	DC	
		Brand	HIGHLY	
Indoor	Fan motor	Model	YYK18-4B	
		Power input	W	18
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1330
	Indoor fan	Dia. / Length	mm	Ø92 / 647
		Indoor Air Circulation (m³/h)	m³/h	880
	Indoor Noise Level dB		dB(A)	38/35/32/29
	Net Dimension (LxWxH)		mm	900x310x225
	Packing Dimension (LxWxH)		mm	950x380x290
Net Weight/Gross Weight		Kg	9,5/11,2	
Outdoor	Fan motor	Model	YDK31-6B	
		Power input	W	31
		Capacity	uF	2.5
		Outdoor Fan Speed RPM	r/min	820
	Outdoor fan	Length	mm	421
	Outdoor Noise Level dB		dB(A)	52
	Net Dimension (LxWxH)		mm	802x535x298
	Packing Dimension (LxWxH)		mm	920x400x620
	Net Weight/Gross Weight		Kg	33.5/36,4
	Refrigerant type/weight		g	R410A/1030
Max. Discharge/Max. Suction pressure		Mpa	4/1	
Refrigerant piping	Liquid side / Gas side	mm	Ø6.35(0,5) / Ø12.7(0,7)	
	Max. refrigerant pipe length / Max. difference in level	m	18/6	