

## TESLA TA70FFLL-24410A



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer, I FEEL function

<b>Capacity</b>			24000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	7000                              7200	
<b>Power input</b>		W	2325                              2243	
<b>Current input</b>		A	10.1                              9.75	
<b>EER-COP</b>		W/W	3.01                              3.21	
<b>Energy Class</b>			A                                      A	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	2900	
<b>Max. current</b>		A	16.5	
<b>Compressor</b>		Model	ASG240V1VMU	
		Type (Rotary/Piston/scroll)	ROTARY	
		Brand	GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	YYK25-4D	
		Power input	W	25
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	1230
	<b>Indoor fan</b>	Dia. / Length	mm	Ø107.9 / 661
	<b>Indoor Air Circulation (m³/h)</b>		m³/h	1050
	<b>Indoor Noise Level dB</b>		dB(A)	40/37/34/31
	<b>Net Dimension (LxWxH)</b>		mm	970x315x235
	<b>Packing Dimension (LxWxH)</b>		mm	1047x385x317
<b>Net Weight/Gross Weight</b>		Kg	11.5/14,3	
<b>Outdoor</b>	<b>Fan motor</b>	Model	YDK69-6A	
		Power input	W	69
		Capacity	uF	4
		Outdoor Fan Speed RPM	r/min	830
	<b>Outdoor fan</b>	Dia. / Length	mm	Ø470 / 140
	<b>Outdoor Noise Level dB</b>		dB(A)	55
	<b>Net Dimension (LxWxH)</b>		mm	825x655x310
	<b>Packing Dimension (LxWxH)</b>		mm	945x725x435
	<b>Net Weight/Gross Weight</b>		Kg	46/50,2
<b>Refrigerant type/weight</b>		g	R410/1500	
<b>Design pressure (Hi/Low)</b>		Mpa	4.15/1.15	
<b>Refrigerant piping</b>		Liquid side / Gas side	mm	Ø6.35(0,5) / Ø15,88(0,75)
		Max. refrigerant pipe length /	m	18/6
		Max. difference in level		