

## TESLA TA71FFML-2432IA



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), I FEEL function

<b>Capacity</b>			24000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	7000 (1400~7300)                      7000 (900~7100)	
<b>Power input</b>		W	2200    1960	
<b>Current input</b>		A	9.75    8.67	
<b>SEER-SCOP/ Energy Class</b>		W/W	6,89/ A++                                      4,11/A+	
<b>Operating range (°C)</b>			14 - 43°C                                      -15 - 30°C	
<b>Dehumidifying</b>		Kg/h	2.3	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	3700	
<b>Max. current</b>		A	16	
<b>Compressor</b>		Model	GTD186UKQA9LT6	
		Type	DC	
		Brand	HIGHLY	
<b>Indoor</b>	<b>Fan motor</b>	Model	YYK50-4	
		Power input	W	50
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	1080
	Indoor fan	Dia. / Length	mm	∅107.9x839
	Indoor Air Circulation (m³/h)		m³/h	1150
	Indoor Noise Level dB		dB(A)	48
	Net Dimension (LxWxH)		mm	1082x330x233
	Packing Dimension (LxWxH)		mm	1155x397x312
Net Weight/Gross Weight		Kg	15/16,8	
<b>Outdoor</b>	<b>Fan motor</b>	Model	D-69-8	
		Power input	W	69
		Capacity	uF	4
		Outdoor Fan Speed RPM	r/min	800
	Outdoor fan	Length	mm	528
	Outdoor Noise Level dB		dB(A)	60
	Net Dimension (LxWxH)		mm	730x545x285
	Packing Dimension (LxWxH)		mm	1155x397x312
	Net Weight/Gross Weight		Kg	45/48,2
	Refrigerant type/weight		g	R32/1440
Max. Discharge/Max. Suction pressure		Mpa	4,28/1,18	
<b>Refrigerant piping</b>	Liquid side / Gas side	mm	6.35 (1/4)/15.88 (5/8)	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	