TESLA
TT26X81-0932IAW

FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, Wi-Fi included, I FEEL function

Capacity				9000BTU	
Rated volt and frequency			V/Hz	220-240V~/50HZ	
Mode				**Cooling**	**Heating**
Rated capacity			W	2600 (940~3320)	2610 (940~3380)
Power input			W	750	752
Current input			A	4.00	4.10
SEER-SCOP/ Energy Class			W/W	6,1/ A++	4,0/A+
Operating range (°C)				0 - 53°C	-20°C - 30°C
Dehumidifying			Kg/h	0.9	
Degree of protection (IN) / (OUT)			(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)			Class I / Class II	I/I	
Max. input consumption			W	1040	
Max. current			A	4.8	
Compressor		Model		KSN98D32UEZ	
		Type		Rotary	
		Brand		GMCC	
Indoor	Fan motor	Model		1170030067G	
		Power input	**W**	20W output	
		Capacity	**uF**	1.5	
		Indoor Fan Speed RPM	**r/min**	≤1320	
	Indoor fan	Dia. / Length	**mm**	Φ92×578	
	Indoor Air Circulation (m^3/h)		**m^3/h**	420	
	Indoor Noise Level dB		**dB(A)**	50/43/35/32	
	Net Dimension (L×W×H)		**mm**	698x255x190	
	Packing Dimension (L×W×H)		**mm**	764×325×257	
	Net Weight/Gross Weight		**Kg**	8,5/10	
Outdoor	Fan motor	Model		1170040162AB	
		Power input	**W**	33W output	
		Capacity	**uF**	/	
		Outdoor Fan Speed RPM	**r/min**	≤1000	
	Outdoor fan	Length	**mm**	φ384×134	
	Outdoor Noise Level dB		**dB(A)**	40/33/25/22	
	Net Dimension (L×W×H)		**mm**	715x240x492	
	Packing Dimension (L×W×H)		**mm**	818×325×520	
	Net Weight/Gross Weight		**Kg**	27,0/28,5	
	Refrigerant type/weight		**g**	R32/530	
	Max. Discharge/Max. Suction pressure		**Mpa**	3.7/1.2	
Refrigerant piping		Liquid side / Gas side	**mm**	6,35/9,52	
		Max. refrigerant pipe length / Max. difference in level	**m**	25/10	