

TESLA TT27X81-09410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, I FEEL function

Capacity			9000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	2680 2700	
Power input		W	820 775	
Current input		A	3.80 3.60	
EER-COP/ Energy Class		W/W	3,22/ A 3,61/ A	
Operating range (°C)		°C	0 - 43°C -5°C - 24°C	
Dehumidifying		Kg/h	1.0	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1060	
Max. current		A	4.9	
Compressor		Model	ASM93V11VDZ	
		Type (Rotary/Piston/scroll)	Rotary	
		Brand	GMCC	
Indoor	Fan motor	Model	1170030047F	
		Power input	W 14W output	
		Capacity	uF 2	
		Indoor Fan Speed RPM	r/min ≤1300	
	Indoor fan	Dia. / Length	mm φ92×578	
	Indoor Air Circulation (m³/h)		m³/h	550
	Indoor Noise Level dB		dB(A)	34/36/39/42
	Net Dimension (L×W×H)		mm	777×250×201
	Packing Dimension (L×W×H)		mm	850×320×275
	Net Weight/Gross Weight		Kg	7/9
Outdoor	Fan motor	Model	1170040062	
		Power input	W 25W output	
		Capacity	uF 2	
		Outdoor Fan Speed RPM	r/min ≤895	
	Outdoor fan	Dia. / Length	mm φ320×119	
	Outdoor Noise Level dB		dB(A)	42/46/48/50
	Net Dimension (L×W×H)		mm	654×507×276
	Packing Dimension (L×W×H)		mm	700×545×300
	Net Weight/Gross Weight		Kg	21/23
	Refrigerant type/weight		g	R410A/560g(2088)
Design pressure (Hi/Low)		Mpa	4.5/1.9	
Refrigerant piping	Liquid side / Gas side		mm 6,35/9,52	
	Max. refrigerant pipe length / Max. difference in level		m 15/5	