



## Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

<b>Capacity</b>			9000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>		W	2490                              2640
<b>Power input</b>		W	775                                730
<b>Current input</b>		A	3,60                               3,40
<b>EER-COP/ Energy Class</b>		W/W	3,21/ A                              3,61/ A
<b>Operating range</b>		(°C)	15 - 43°C                              -7°C - 24°C
<b>Energy consumption (per year, based on standard test results)</b>		kwh	388
<b>Dehumidifying</b>		Kg/h	1,0
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I
<b>Max. input consumption</b>		W	1250
<b>Max. current</b>		A	6,8
<b>Compressor</b>		Model	ASM93V11VDZ
		Type	Rotary
		Brand	GMCC
<b>Indoor</b>	<b>Fan motor</b>	Model	22001-000273
		Power input	W                                      14W output
		Capacity	uF                                      2
		Indoor Fan Speed RPM	r/min                                      ≤1300
	<b>Indoor fan</b>	Dia. / Length	mm                                      φ92×578
	<b>Indoor Air Circulation</b>	m <sup>3</sup> /h	430
	<b>Indoor Noise Level dB</b>	dB(A)	35/33/29/27/25
	<b>Net Dimension (L×W×H)</b>	mm	698×255×190
<b>Packing Dimension (L×W×H)</b>	mm	764×325×257	
<b>Net Weight/Gross Weight</b>	Kg	6,5/8,5	
<b>Outdoor</b>	<b>Fan motor</b>	Model	22001-000007
		Power input	W                                      25W output
		Capacity	uF                                      2
		Outdoor Fan Speed RPM	r/min                                      ≤895
	<b>Outdoor fan</b>	Length	mm                                      φ320×119
	<b>Outdoor Noise Level dB</b>	dB(A)	48
	<b>Net Dimension (L×W×H)</b>	mm	712×276×459
	<b>Packing Dimension (L×W×H)</b>	mm	765×310×481
	<b>Net Weight/Gross Weight</b>	Kg	22,5/25
<b>Refrigerant type/weight</b>	Kg	R410A/0.430	
<b>Max. Discharge/Max. Suction pressure</b>	Mpa	4.5/1.9	
<b>Refrigerant piping</b>	Liquid side / Gas side	mm	6,35/9,52
	Max. refrigerant pipe length / Max. difference in level	m	15/5