

TESLA TT27XC1-09410B



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, I FEEL function

Capacity			9000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	2680 2700
Power input		W	850 800
Current input		A	3.90 3.70
EER-COP/ Energy Class		W/W	3,11/ B 3,51/ B
Operating range (°C)		°C	0 - 43°C -5°C - 24°C
Dehumidifying		Kg/h	1.0
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1120
Max. current		A	3.9
Compressor		Model	39A183BD&59KA
		Type (Rotary/Piston/scroll)	Rotary
		Brand	RECHI
Indoor	Fan motor	Model	1170030047F
		Power input	W 14W output
		Capacity	uF 2
		Indoor Fan Speed RPM	r/min ≤1300
	Indoor fan	Dia. / Length	mm φ92×494
	Indoor Air Circulation (m³/h)		m³/h 420
	Indoor Noise Level dB		dB(A) 34/36/39/42
	Net Dimension (L×W×H)		mm 698×255×190
	Packing Dimension (L×W×H)		mm 764×325×267
Net Weight/Gross Weight		Kg 6/8	
Outdoor	Fan motor	Model	1170040071
		Power input	W 20W output
		Capacity	uF 2
		Outdoor Fan Speed RPM	r/min ≤850
	Outdoor fan	Dia. / Length	mm φ320×119
	Outdoor Noise Level dB		dB(A) 42/46/48/50
	Net Dimension (L×W×H)		mm 654×507×276
	Packing Dimension (L×W×H)		mm 700×545×300
	Net Weight/Gross Weight		Kg 21/23
Refrigerant type/weight		g R410A/420g(2088)	
Design pressure (Hi/Low)		Mpa 4.5/1.9	
Refrigerant piping		Liquid side / Gas side	mm 6,35/9,52
		Max. refrigerant pipe length / Max. difference in level	m 15,0/5,0