

TESLA TT34X21-1232IAWPC



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, Wi-Fi Included, I FEEL function

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3500 (1000~3770) 3520 (1000~3810)	
Power input		W	1130 922	
Current input		A	5.80 4.70	
SEER-SCOP/ Energy Class		W/W	6,1/ A++ 4,0/A+	
Operating range (°C)			0 - 53°C -20°C - 30°C	
Dehumidifying		Kg/h	1.2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1720	
Max. current		A	10	
Compressor		Model	KSN98D32UEZ	
		Type	Rotary	
		Brand	GMCC	
Indoor	Fan motor	Model	1170030067G	
		Power input	W	20W output
		Capacity	uF	2
		Indoor Fan Speed RPM	r/min	≤1320
	Indoor fan	Dia. / Length	mm	φ92×578
	Indoor Air Circulation (m³/h)	m³/h		550/550
	Indoor Noise Level dB	dB(A)		22/25/33/37/40
	Net Dimension (L×W×H)	mm		777×250×201
Packing Dimension (L×W×H)	mm		850×320×275	
Net Weight/Gross Weight	Kg		8/10.5	
Outdoor	Fan motor	Model	1170040162AB	
		Power input	W	33W output
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	≤1000
	Outdoor fan	Length	mm	φ384×134
	Outdoor Noise Level dB	dB(A)		29/33/39/46/50
	Net Dimension (L×W×H)	mm		777×498×290
	Packing Dimension (L×W×H)	mm		818×520×325
Net Weight/Gross Weight	Kg		22/25	
Refrigerant type/weight	g		R32/550g/675	
Max. Discharge/Max. Suction pressure	Mpa		3.7/1.2	
Refrigerant piping	Liquid side / Gas side	mm	6.35/9.52	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	