

## TESLA TT34XC1-1232IAW



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, Wi-Fi Included, I FEEL function

<b>Capacity</b>			12000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	3500 (1000~3770)                      3520 (1000~3810)	
<b>Power input</b>		W	1130    922	
<b>Current input</b>		A	5.80    4.70	
<b>SEER-SCOP/ Energy Class</b>		W/W	6,1/ A++                                      4,0/A+	
<b>Operating range (°C)</b>			0 - 53°C                                      -20°C - 30°C	
<b>Dehumidifying</b>		Kg/h	1.2	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	1720	
<b>Max. current</b>		A	10	
<b>Compressor</b>		Model	KSN98D32UEZ	
		Type	Rotary	
		Brand	GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	1170030067G	
		Power input	W 20W output	
		Capacity	uF 2	
		Indoor Fan Speed RPM	r/min ≤1320	
	Indoor fan	Dia. / Length	mm φ92×578	
	Indoor Air Circulation (m³/h)		m³/h	550/550
	Indoor Noise Level dB		dB(A)	22/25/33/37/40
	Net Dimension (L×W×H)		mm	777×250×201
Packing Dimension (L×W×H)		mm	850×320×275	
Net Weight/Gross Weight		Kg	8/10.5	
<b>Outdoor</b>	<b>Fan motor</b>	Model	1170040162AB	
		Power input	W 33W output	
		Capacity	uF /	
		Outdoor Fan Speed RPM	r/min ≤1000	
	Outdoor fan	Length	mm φ384×134	
	Outdoor Noise Level dB		dB(A)	29/33/39/46/50
	Net Dimension (L×W×H)		mm	777×498×290
	Packing Dimension (L×W×H)		mm	818×520×325
	Net Weight/Gross Weight		Kg	22/25
	Refrigerant type/weight		g	R32/550g/675
Max. Discharge/Max. Suction pressure		Mpa	3.7/1.2	
<b>Refrigerant piping</b>		Liquid side / Gas side	mm	6.35/9.52
		Max. refrigerant pipe length / Max. difference in level	m	25/10