TESLA
TT35X21-12410IA

FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, I FEEL function

Capacity				12000BTU	
Rated volt and frequency			V/Hz	220-240V~/50HZ	
Mode				**Cooling**	**Heating**
Rated capacity			W	3520 (1020~3860)	3560(1020~4130)
Power input			W	1134	975
Current input			A	5.70	5.30
SEER-SCOP/ Energy Class			W/W	6,2/ A++	4,0/A+
Operating range (°C)				15 - 53°C	-20°C - 30°C
Dehumidifying			Kg/h	1.2	
Degree of protection (IN) / (OUT)			(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)			Class I / Class II	I/I	
Max. input consumption			W	1430	
Max. current			A	7	
Compressor		Model		39A23MYJ&FJKD	
		Type		Rotary	
		Brand		RECHI	
Indoor	Fan motor	Model		1170030067G	
		Power input	**W**	20W output	
		Capacity	**uF**	2	
		Indoor Fan Speed RPM	**r/min**	≤11320	
	Indoor fan	Dia. / Length	**mm**	φ92×578	
	Indoor Air Circulation (m^3/h)		**m^3/h**	550/550	
	Indoor Noise Level dB		**dB(A)**	22/26/29/34/40	
	Net Dimension (L×W×H)		**mm**	777×250×201	
	Packing Dimension (L×W×H)		**mm**	850×320×275	
	Net Weight/Gross Weight		**Kg**	8.5/10.5	
Outdoor	Fan motor	Model		1170040162AB	
		Power input	**W**	33W output	
		Capacity	**uF**	/	
		Outdoor Fan Speed RPM	**r/min**	≤1000rpm	
	Outdoor fan	Length	**mm**	φ390×112	
	Outdoor Noise Level dB		**dB(A)**	32/37/43/47/50	
	Net Dimension (L×W×H)		**mm**	754×300×552	
	Packing Dimension (L×W×H)		**mm**	798×321×575	
	Net Weight/Gross Weight		**Kg**	25/28	
	Refrigerant type/weight		**g**	R410A/780g/2088	
	Max. Discharge/Max. Suction pressure		**Mpa**	4.5/1.9	
Refrigerant piping		Liquid side / Gas side	**mm**	6,35/9,52	
		Max. refrigerant pipe length / Max. difference in level	**m**	25/10	