

TESLA TT35X21-12410IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, I FEEL function

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3520 (1020~3860) 3600(1020~4200)	
Power input		W	1134 975	
Current input		A	5.70 5.30	
SEER-SCOP/ Energy Class		W/W	6,2/ A++ 4,0/A+	
Operating range (°C)			15 - 53°C -20°C - 30°C	
Dehumidifying		Kg/h	1.2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1430	
Max. current		A	7	
Compressor		Model	39A23MYJ&FJKD	
		Type	Rotary	
		Brand	RECHI	
Indoor	Fan motor	Model	1170030067G	
		Power input	W 20W output	
		Capacity	uF 2	
		Indoor Fan Speed RPM	r/min ≤11320	
	Indoor fan	Dia. / Length	mm φ92×578	
		Indoor Air Circulation (m³/h)	m³/h 550/550	
	Indoor Noise Level dB		dB(A)	22/26/29/34/40
	Net Dimension (L×W×H)		mm	772x246x202
	Packing Dimension (L×W×H)		mm	858x328x281
Net Weight/Gross Weight		Kg	8.5/10.5	
Outdoor	Fan motor	Model	1170040162AB	
		Power input	W 33W output	
		Capacity	uF /	
		Outdoor Fan Speed RPM	r/min ≤1000rpm	
	Outdoor fan	Length	mm φ390×112	
	Outdoor Noise Level dB		dB(A)	32/37/43/47/50
	Net Dimension (L×W×H)		mm	785x285x495
	Packing Dimension (L×W×H)		mm	822x327x533
	Net Weight/Gross Weight		Kg	25/28
	Refrigerant type/weight		g	R410A/780g/2088
Max. Discharge/Max. Suction pressure		Mpa	4.5/1.9	
Refrigerant piping	Liquid side / Gas side	mm	6,35/9,52	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	