

### I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



### Self-diagnostic

The air conditioner is able to monitor its operations and identify problematic or faulty parts. If they're found, the system will switch off automatically, while the error code will be displayed on the indoor unit.



### Anti-fungus

The air conditioner will start the Anti-fungus feature after exiting cooling and dehumidifying mode. It helps prevent fungi and bacteria from spreading in order to maintain a healthy environment.



### Auto restart

The AC can automatically memorize the operation settings when power goes out unexpectedly, so it can restore them and continue working when the energy supply is back on.



### Washable filter

The indoor unit filter can be removed and easily washed at any time.



### Features

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, I FEEL function

<b>Capacity</b>			12000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>		W	3230      3370
<b>Power input</b>		W	1005      934
<b>Current input</b>		A	4,70      4,40
<b>EER-COP/ Energy Class</b>		W/W	3,21/ A      3,61/ A
<b>Operating range</b>		(°C)	15 - 43°C      -7°C - 24°C
<b>Energy consumption (per year, based on standard test results)</b>		kwh	503
<b>Dehumidifying</b>		Kg/h	1,2
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I
<b>Max. input consumption</b>		W	1760
<b>Max. current</b>		A	9,5
<b>Compressor</b>		Model	ASM93V11VDZ
		Type	Rotary
		Brand	GMCC
<b>Indoor</b>	<b>Fan motor</b>	Model	22001-000273
		Power input	W      14W output
		Capacity	uF      2
		Indoor Fan Speed RPM	r/min      ≤1300
	Indoor fan	Dia. / Length	mm      ø92×578
	Indoor Air Circulation		m³/h      550
	Indoor Noise Level dB		dB(A)      42/40/37/34/31
	Net Dimension (L×W×H)		mm      777×250×201
	Packing Dimension (L×W×H)		mm      850×320×275
	Net Weight/Gross Weight		Kg      7,5/9,5
<b>Outdoor</b>	<b>Fan motor</b>	Model	22001-000007
		Power input	W      25W output
		Capacity	uF      2
		Outdoor Fan Speed RPM	r/min      ≤895
	Outdoor fan	Length	mm      ø320×119
	Outdoor Noise Level dB		dB(A)      50
	Net Dimension (L×W×H)		mm      777×290×498
	Packing Dimension (L×W×H)		mm      818×325×520
	Net Weight/Gross Weight		Kg      25/28
	Refrigerant type/weight		g      R410A/0.570
<b>Refrigerant piping</b>		Max. Discharge/Max. Suction pressure	Mpa      4.5/1.9
		Liquid side / Gas side	mm      6,35/9,52
		Max. refrigerant pipe length / Max. difference in level	m      15/5