



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	3230 3370
Power input		W	1005 934
Current input		A	4,70 4,40
EER-COP/ Energy Class		W/W	3,21/ A 3,61/ A
Operating range		(°C)	15 - 43°C -7°C - 24°C
Energy consumption (per year, based on standard test results)		kwh	503
Dehumidifying		Kg/h	1,2
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1760
Max. current		A	9,5
Compressor		Model	ASM93V11VDZ
		Type	Rotary
		Brand	GMCC
Indoor	Fan motor	Model	22001-000273
		Power input	W 14W output
		Capacity	uF 2
		Indoor Fan Speed RPM	r/min ≤1300
	Indoor fan	Dia. / Length	mm φ92×578
	Indoor Air Circulation	m ³ /h	550
	Indoor Noise Level dB	dB(A)	42/40/37/34/31
	Net Dimension (L×W×H)	mm	777×250×201
	Packing Dimension (L×W×H)	mm	850×320×275
Net Weight/Gross Weight	Kg	7,5/9,5	
Outdoor	Fan motor	Model	22001-000007
		Power input	W 25W output
		Capacity	uF 2
		Outdoor Fan Speed RPM	r/min ≤895
	Outdoor fan	Length	mm φ320×119
	Outdoor Noise Level dB	dB(A)	50
	Net Dimension (L×W×H)	mm	777×290×498
	Packing Dimension (L×W×H)	mm	818×325×520
	Net Weight/Gross Weight	Kg	25/28
Refrigerant type/weight	Kg	R410A/0.570	
Max. Discharge/Max. Suction pressure	Mpa	4.5/1.9	
Refrigerant piping	Liquid side / Gas side	mm	6,35/9,52
	Max. refrigerant pipe length / Max. difference in level	m	15/5