

TESLA TT35XC1-12410B



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, I FEEL function

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3520 3700	
Power input		W	1130 1050	
Current input		A	5.20 4.80	
EER-COP/ Energy Class		W/W	3,12/ B 3,51/ B	
Operating range (°C)		°C	0 - 43°C -5°C - 24°C	
Dehumidifying		Kg/h	1.0	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1470	
Max. current		A	6.7	
Compressor		Model	44A263BK-FJKC	
		Type (Rotary/Piston/scroll)	Rotary	
		Brand	RECHI	
Indoor	Fan motor	Model	1170030047F	
		Power input	W	14W output
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	≤1300
	Indoor fan	Dia. / Length	mm	φ92×578
	Indoor Air Circulation (m³/h)		m³/h	550
	Indoor Noise Level dB		dB(A)	34/36/39/42
	Net Dimension (L×W×H)		mm	777×250×201
	Packing Dimension (L×W×H)		mm	850×320×275
	Net Weight/Gross Weight		Kg	7/9
Outdoor	Fan motor	Model	GZSDJ-03	
		Power input	W	25W output
		Capacity	uF	2.5
		Outdoor Fan Speed RPM	r/min	≤860
	Outdoor fan	Dia. / Length	mm	φ408×132
	Outdoor Noise Level dB		dB(A)	43/48/50/52
	Net Dimension (L×W×H)		mm	754×300×552
	Packing Dimension (L×W×H)		mm	798×321×575
	Net Weight/Gross Weight		Kg	27/29
	Refrigerant type/weight		g	R410A/630g(2088)
Design pressure (Hi/Low)		Mpa	4.5/1.9	
Refrigerant piping	Liquid side / Gas side	mm	6,35/9,52	
	Max. refrigerant pipe length / Max. difference in level	m	15/5	