



## Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

<b>Capacity</b>			12000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>		W	3230                              3370
<b>Power input</b>		W	1073                              988
<b>Current input</b>		A	5,00                              4,60
<b>EER-COP/ Energy Class</b>		W/W	3,01 / B                      3,41 / B
<b>Operating range</b>		(°C)	15 - 43°C                      -7°C - 24°C
<b>Energy consumption (per year, based on standard test results)</b>		kwh	537
<b>Dehumidifying</b>		Kg/h	1,2
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I
<b>Max. input consumption</b>		W	1760
<b>Max. current</b>		A	9,5
<b>Compressor</b>		Model	ASM93V11VDZ
		Type	Rotary
		Brand	GMCC
<b>Indoor</b>	<b>Fan motor</b>	Model	22001-000273
		Power input	W                              14W output
		Capacity	uF                              2
		Indoor Fan Speed RPM	r/min                              ≤1300
	Indoor fan	Dia. / Length	mm                              φ92×578
	Indoor Air Circulation	m <sup>3</sup> /h	550
	Indoor Noise Level dB	dB(A)	42/40/37/34/31
	Net Dimension (L×W×H)	mm	777×250×201
Packing Dimension (L×W×H)	mm	850×320×275	
Net Weight/Gross Weight	Kg	7,5/9,5	
<b>Outdoor</b>	<b>Fan motor</b>	Model	22001-000007
		Power input	W                              25W output
		Capacity	uF                              2
		Outdoor Fan Speed RPM	r/min                              ≤895
	Outdoor fan	Length	mm                              φ320×119
	Outdoor Noise Level dB	dB(A)	50
	Net Dimension (L×W×H)	mm	777×290×498
	Packing Dimension (L×W×H)	mm	818×325×520
	Net Weight/Gross Weight	Kg	25/28
	Refrigerant type/weight	Kg	R410A/0.570
Max. Discharge/Max. Suction pressure	Mpa	4.5/1.9	
<b>Refrigerant piping</b>	Liquid side / Gas side	mm	6,35/9,52
	Max. refrigerant pipe length / Max. difference in level	m	15/5