

TESLA TT68X21-24410IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, I FEEL function

Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	6810 (1500~7310) 6850(1500~5800)	
Power input		W	1940 1988	
Current input		A	8.50 8.70	
SEER-SCOP/ Energy Class		W/W	6,3/ A++ 4,0/A+	
Operating range (°C)			14 - 53°C -20°C - 30°C	
Dehumidifying		Kg/h	2.4	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2900	
Max. current		A	12	
Compressor		Model	ATN150D42UFZ	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	GGSDJ-23A	
		Power input	W	
		Capacity	uF	
		Indoor Fan Speed RPM	r/min	
	Indoor fan	Dia. / Length	mm	φ111.5X1010
		Indoor Air Circulation (m³/h)	m³/h	1000/1100
	Indoor Noise Level dB		dB(A)	30/38/41/44
	Net Dimension (LxWxH)		mm	1010×315×220
	Packing Dimension (LxWxH)		mm	1096×390×297
Net Weight/Gross Weight		Kg	13/16	
Outdoor	Fan motor	Model	GZSDJ-31(DC)	
		Power input	W	
		Capacity	uF	
		Outdoor Fan Speed RPM	r/min	
	Outdoor fan	Length	mm	φ536×153
	Outdoor Noise Level dB		dB(A)	47/51/55/58
	Net Dimension (LxWxH)		mm	968×655×375
	Packing Dimension (LxWxH)		mm	1015×715×425
	Net Weight/Gross Weight		Kg	45/48
	Refrigerant type/weight		g	R410A/2000/2088
Max. Discharge/Max. Suction pressure		Mpa	4.5/1.9	
Refrigerant piping	Liquid side / Gas side	mm	6.35/15.88	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	