

TESLA TA36FFLL-1232IAPC



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), I FEEL function, Instalation Kit

Capacity		12000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity		3500(1400-3520)	3500(1100-3750)
Power input		997(450-1500)	970(400-1350)
Current input		4.33(2.0-7.5)	4.3(1.6-7.0)
SEER-SCOP/ Energy Class		6.17/A++	4.06/A+
Operating range (°C)		14 - 43°C	-15 - 30°C
Dehumidifying		Kg/h 1.1	
Degree of protection (IN) / (OUT)		(IP) IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 1800	
Max. current		A 8.5	
Compressor		ASK103D53UFZE	
		DC	
		GMCC	
Indoor	Fan motor	Model	YYK18-4B
		Power input	W 18
		Capacity	uF 1.5
		Indoor Fan Speed RPM	r/min 1250
	Indoor fan	Dia. / Length	mm ø97.8 / 558
	Indoor Air Circulation (m³/h)		m³/h 480
	Indoor Noise Level dB		dB(A) 33/29/27/24
	Net Dimension (LxWxH)		mm 727x285x195
	Packing Dimension (LxWxH)		mm 815x345x275
	Net Weight/Gross Weight		Kg 7,8/9,3
Outdoor	Fan motor	Model	YDK25-6B
		Power input	W 25
		Capacity	uF 1.5
		Outdoor Fan Speed RPM	r/min 820
	Outdoor fan	Length	mm 390
	Outdoor Noise Level dB		dB(A) 52
	Net Dimension (LxWxH)		mm 815x340x540
	Packing Dimension (LxWxH)		mm 845x355x600
	Net Weight/Gross Weight		Kg 27,8/30,4
	Refrigerant type/weight		g R32/600
Max. Discharge/Max. Suction pressure		Mpa 4/1	
Refrigerant piping	Liquid side / Gas side	mm	φ6.35(0,5) / φ9.52(0,6)
	Max. refrigerant pipe length / Max. difference in level	m	18/6