

TESLA TA36FFLL-12410IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), I FEEL function

Capacity		12000BTU		
Rated volt and frequency		V/Hz		
Mode				
Rated capacity		Cooling	Heating	
Power input		3200(1400-3520)	3500(1100-3750)	
Current input		997(450-1500)	970(400-1350)	
SEER-SCOP/ Energy Class		4.33(2.0-7.5)	4.3(1.6-7.0)	
Operating range (°C)		6.17/A++	4.06/A+	
Dehumidifying		14 - 43°C	-15 - 30°C	
Degree of protection (IN) / (OUT)		Kg/h		
Class of electric protection (IN) / (OUT)		(IP)		
Max. input consumption		IPX4/IPX4		
Max. current		Class I / Class II		
Compressor		I/I		
		W		
		A		
		ASK103D53UFZE		
		DC		
		GMCC		
Indoor	Fan motor	Model	YYK18-4B	
		Power input	18	
		Capacity	1.5	
		Indoor Fan Speed RPM	1250	
	Indoor fan	Dia. / Length	mm	Ø97.8/558
		Indoor Air Circulation (m³/h)	m³/h	480
	Indoor Noise Level dB		dB(A)	33/29/27/24
	Net Dimension (LxWxH)		mm	700x285x188
	Packing Dimension (LxWxH)		mm	750x355x260
	Net Weight/Gross Weight		Kg	7,8/9,3
Outdoor	Fan motor	Model	YDK25-6B	
		Power input	25	
		Capacity	1.5	
		Outdoor Fan Speed RPM	820	
	Outdoor fan	Length	mm	390
	Outdoor Noise Level dB		dB(A)	52
	Net Dimension (LxWxH)		mm	720x545x255
	Packing Dimension (LxWxH)		mm	835x382x600
	Net Weight/Gross Weight		Kg	27,8/30,4
	Refrigerant type/weight		g	R410A/710
Max. Discharge/Max. Suction pressure		Mpa	4/1	
Refrigerant piping	Liquid side / Gas side	mm	Ø6.35(0,5) / Ø9.52(0,6)	
	Max. refrigerant pipe length / Max. difference in level	m	18/6	