

TESLA TA36FFML-1232IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), I FEEL function

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3500(800~3500) 3500(1000~3600)	
Power input		W	1090 970	
Current input		A	4.82 4.28	
SEER-SCOP/ Energy Class		W/W	6.1/A++ 4.07/A+	
Operating range (°C)			14 - 43°C -15 - 30°C	
Dehumidifying		Kg/h	1.2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1900	
Max. current		A	9.5	
Compressor		Model	KSK89D59UFZE	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK12-4B	
		Power input	W	
		Capacity	uF	
		Indoor Fan Speed RPM	r/min	
	Indoor fan	Dia. / Length	mm	
			Ø97.8 / 558	
	Indoor Air Circulation (m³/h)		m³/h	560
	Indoor Noise Level dB		dB(A)	53
	Net Dimension (LxWxH)		mm	770x280x200
Packing Dimension (LxWxH)		mm	840x345x280	
Net Weight/Gross Weight		Kg	8/10.5	
Outdoor	Fan motor	Model	D-24-8	
		Power input	W	
		Capacity	uF	
		Outdoor Fan Speed RPM	r/min	
	Outdoor fan	Length	mm	
			390	
	Outdoor Noise Level dB		dB(A)	59
	Net Dimension (LxWxH)		mm	800x315x545
	Packing Dimension (LxWxH)		mm	840x365x600
	Net Weight/Gross Weight		Kg	25/27.5
Refrigerant type/weight		g	R32/600	
Max. Discharge/Max. Suction pressure		Mpa	4,28/1,18	
Refrigerant piping	Liquid side / Gas side	mm	6.35 (1/4) / 9,53 (3/8)	
	Max. refrigerant pipe length / Max. difference in level	m	15/10	