



## **B0900MX**

















70L BI Oven / 2 Glass enamel door / 120mm control panel / digital timer / 9 functions including light / electrical control / cooling fan / Energy A / Metal handle and knob



Source         Electrical           Cavity size         70 L           Valtage         220-240 voits, 3 wire 50/60 Hz           Max current         230V-13A 240V-15A           Appearance         Fully glass           Energy efficiency rate         A           Cavity Size (WxDxH) mm         457x410x346.5           Oven Size (WxDxH) mm         648x688x670           Net Weight (log)         28.5           Gross Weight (Carton box) (kg)         315           Temperature range         50/250°C           Timer         Digital           Cooling Fan         YES           CONTROL PANEL         E           TECHNICAL & INTERNAL SPECIFICATION         E sasy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION         Formed           Rack support         Formed           Enamel 2 layers           Inner door plate         Enamel 2 layers           Rack support         Formed           Enamel 2 layers           Door plate         Enamel 2 layers           Enamel 2 layers           Enamel 2 layers           Door plate plement         Concealed           To pheating element         200 W           Convection beating element	FEATURES	
Voltage		Electrical
Voltage         220-240 volts, 3 wire 50/60 Hz           Max current         230V-13A 240V-15A           Appearance         Fully glass           Energy efficiency rate         A           Cavity, Size (WxDxH) mm         457x410x346.5           Oven Size (WxDxH) mm         648x689x.670           Net Weight (kg)         28.5           Gross Weight (Carten box) (kg)         31.5           FUNCTIONS         ************************************	Cavity size	70 L
Max current         230V-13A 240V-15A           Appearance         Fully glass           Lengy efficiency rate         A           Cavity Size (WxDxH) mm         457x410x3465           Oven Size (WxDxH) mm         695x575x595           Pakaging Size (WxDxH) mm         648x688x670           Net Weight (Edg)         28,5           Gross Weight (Carton box) (kg)         31,5           FUNCTIONS         ************************************		220-240 volts, 3 wire 50/60 Hz
Energy efficiency rate         A           Cavity, Size (WxDxH) mm         457x410x346.5           Oven Size (WxDxH) mm         648x688x670           Pakaging Size (WxDxH) mm         648x688x670           Net Weight (kg)         28.5           Gross Weight (Carton box) (kg)         31.5           FUNCTIONS         Temperature range         50/250°C           Timer         Digital           Cooling Fan         YE           CONTROL PANEL         UED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL 8 INTERNAL SPECIFICATION         With metal           Rack support         Formed           Inner door plate         With metal           Rack support         Good wellow           Convention heating element         2000 W           Convection heating element         <		
Energy efficiency rate         A           Cavity, Size (WxDxH) mm         457x410x346.5           Oven Size (WxDxH) mm         648x688x670           Pakaging Size (WxDxH) mm         648x688x670           Net Weight (kg)         28.5           Gross Weight (Carton box) (kg)         31.5           FUNCTIONS         Temperature range         50/250°C           Timer         Digital           Cooling Fan         YE           CONTROL PANEL         UED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL 8 INTERNAL SPECIFICATION         With metal           Rack support         Formed           Inner door plate         With metal           Rack support         Good wellow           Convention heating element         2000 W           Convection heating element         <	Appearance	Fully glass
Cavity Size (WxDxH) mm         \$95x57xx595           Pakaging Size (WxDxH) mm         648x688x670           Net Weight (kg)         28.5           Gross Weight (Carton box) (kg)         31.5           FUNCTIONS           Timer         Digital           Cooling Fan         YES           CONTROL FANEL           LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           Dor plate           Enamel, 2 layers           Inner door plate         Fanmel, 2 layers           Inner door plate         Formed           Eack support         Formed           Enamelled cavity         YES           Botton element         Concealed           Top heating element         950 W           Botton heating element         2000 W           Grill heating element         2000 W           Convection mator         33 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES         1 (put into cavity) <td>Energy efficiency rate</td> <td></td>	Energy efficiency rate	
Oven Size (WxDxH) mm         595x575x595           Pakaging Size (WxDxH) mm         648x688x670           Net Weight (kg)         28,5           Gross Weight (Carton box) (kg)         31.5           FUNCTIONS           Temperature range         50/250°C           Timer         Digital           Cooling Fan         YES           CONTROL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           TOO plate           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         250 W           Bottom heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Floation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES         1		457x410x346.5
Net Weight (kg)         28.5           Gross Weight (Carton box) (kg)         31.5           FUNCTIONS         Temperature range         50/250°C           Timer         Digital           Cooling Fan         YES           CONTROL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Botton element         Concealed           Top heating element         950 W           Botton heating element         100 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection heating element         2000 W           Convection heating element         2000 W           Max power         3000 W           Fivation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES         1(Put into cavity)           Telescopic runner         1(Put into cavity)		595x575x595
Gross Weight (Carton box) (kg)         31,5           FUNCTIONS           Temperature range         50/250°C           Timer         Digital           Cooling Fan         YES           CONTROL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         950 W           Bottom heating element         1100 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Conling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES           Shelf rack         1 (Put into cavity)           Indicator         1 (In control pan	Pakaging Size (WxDxH) mm	648x688x670
FUNCTIONS           Temperature range         50/250°C           Timer         Digital           Cooling Fan         YES           CONTROIL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           Dor plate           Rack support         Formed           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         950 W           Bottom heating element         2000 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES           Stelf rack         1 (Put into cavity)           Indicator         1 (Put into cavity)	Net Weight (kg)	28,5
Temperature range         50/250°C           Timer         Digital           Cooling Fan         YES           CONTROL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         2000 W           Bottom heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES           Shelf rack         1 (Put into cavity)           Indicator         1 (Iput into cavity)	Gross Weight (Carton box) (kg)	31,5
Timer         Digital           Cooling Fan         YES           CONTROL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION         Technical           Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         950 W           Bottom heating element         100 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES         STANDARD ACCESSORIES           Stelf rack         1 (Put into cavity)           Baking pan (enameled)         1 (Put into cavity)           Indicator         1 (In control panel)           Telescopic runner         1 (Put into cavit	FUNCTIONS	
Timer         Digital           Cooling Fan         YES           CONTROL PANEL           Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION         Technical           Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         950 W           Bottom heating element         100 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES         STANDARD ACCESSORIES           Stelf rack         1 (Put into cavity)           Baking pan (enameled)         1 (Put into cavity)           Indicator         1 (In control panel)           Telescopic runner         1 (Put into cavit	Temperature range	50/250°C
CONTROL PANELDisplayLEDControllerEasy-tronic, 4 Touch KeysTECHNICAL & INTERNAL SPECIFICATIONDoor plateEnamel, 2 layersInner door plateWith metalRack supportFormedEnamelled cavityYESBottom elementConcealedTop heating element950 WBottom heating element2000 WConvection heating element2000 WConvection motor33 WCooling fan23 WOven lamp25 WMax power3000 WFixation kitScrewsForced cooling system and smoke ventilationYESSTANDARD ACCESSORIES1 (Put into cavity)Elescopic runner1 (Put into cavity)Indicator1 (Put into cavity)Telescopic runner1 (Put into cavity)		Digital
Display         LED           Controller         Easy-tronic, 4 Touch Keys           TECHNICAL & INTERNAL SPECIFICATION           Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         950 W           Bottom heating element         1100 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         Screws           STANDARD ACCESSORIES         Standard Marchael           Shelf rack         1 (Put into cavity)           Indicator         1 (In control panel)           Telescopic runner         1 (Put into cavity)	Cooling Fan	YES
Controller Easy-tronic, 4 Touch Keys  TECHNICAL & INTERNAL SPECIFICATION  Door plate Enamel, 2 layers  Inner door plate With metal Rack support Formed  Enamelled cavity YES  Bottom element Concealed  Top heating element 950 W  Bottom heating element 100 W  Grill heating element 2000 W  Convection heating element 2000 W  Convection heating element 230 W  Convection motor 33 W  Cooling fan 23 W  Oven lamp 25 W  Max power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  SHelf rack 1(Put into cavity)  Indicator 1(Put into cavity)  Telescopic runner	CONTROL PANEL	
TECHNICAL & INTERNAL SPECIFICATIONDoor plateEnamel, 2 layersInner door plateWith metalRack supportFormedEnamelled cavityYESBottom elementConcealedTop heating element950 WBottom heating element1100 WGrill heating element2000 WConvection heating element2000 WConvection motor33 WCooling fan23 WOven lamp25 WMax power3000 WFixation kitScrewsForced cooling system and smoke ventilationYESSTANDARD ACCESSORIESShelf rack1 (Put into cavity)Baking pan (enameled)1 (Put into cavity)Indicator1 (Put into cavity)Telescopic runner1 (Put into cavity)	Display	LED
Door plate         Enamel, 2 layers           Inner door plate         With metal           Rack support         Formed           Enamelled cavity         YES           Bottom element         Concealed           Top heating element         950 W           Bottom heating element         1100 W           Grill heating element         2000 W           Convection heating element         2000 W           Convection motor         33 W           Cooling fan         23 W           Oven lamp         25 W           Max power         3000 W           Fixation kit         Screws           Forced cooling system and smoke ventilation         YES           STANDARD ACCESSORIES         1(Put into cavity)           Baking pan (enameled)         1(Put into cavity)           Indicator         1(In control panel)           Telescopic runner         1(Put into cavity)	Controller	Easy-tronic, 4 Touch Keys
Inner door plate With metal Rack support Formed Enamelled cavity YES Bottom element Concealed Top heating element 950 W Bottom heating element 1100 W Grill heating element 2000 W Convection heating element 2000 W Convection heating element 2000 W Convection motor 33 W Cooling fan 23 W Oven lamp 25 W Max. power 3000 W Fixation kit Screws Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES STANDARD ACCESSORIES SHelf rack 1(Put into cavity) Indicator 1(In control panel) Telescopic runner	TECHNICAL & INTERNAL SPECIFICATION	
Rack support Formed  Enamelled cavity YES  Bottom element Concealed  Top heating element 950 W  Bottom heating element 1100 W  Grill heating element 2000 W  Convection heating element 2000 W  Convection motor 33 W  Cooling fan 23 W  Oven lamp 25 W  Max. power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1(Put into cavity)  Indicator 1(Put into cavity)  Indicator 1(Put into cavity)  Telescopic runner	Door plate	Enamel, 2 layers
Enamelled cavity  Bottom element  Concealed  Top heating element  Bottom heating element  Bottom heating element  1100 W  Grill heating element  2000 W  Convection heating element  2000 W  Convection motor  33 W  Cooling fan  23 W  Oven lamp  25 W  Max. power  3000 W  Fixation kit  Screws  Forced cooling system and smoke ventilation  YES  STANDARD ACCESSORIES  Shelf rack  1 [Put into cavity]  Baking pan (enameled)  1 [Put into cavity]  Indicator  1 [Put into cavity]  Indicator  1 [Put into cavity]	Inner door plate	With metal
Bottom element Concealed Top heating element 950 W  Bottom heating element 1100 W  Grill heating element 2000 W  Convection heating element 2000 W  Convection heating element 2000 W  Convection motor 33 W  Cooling fan 23 W  Oven lamp 25 W  Max. power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1(Put into cavity)  Baking pan (enameled) 1(Put into cavity)  Indicator 1(Put into cavity)  Telescopic runner	Rack support	Formed
Top heating element 950 W  Bottom heating element 1100 W  Grill heating element 2000 W  Convection heating element 2000 W  Convection motor 33 W  Cooling fan 23 W  Oven lamp 25 W  Max. power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1(Put into cavity)  Baking pan (enameled) 1(Put into cavity)  Indicator 1(In control panel)  Telescopic runner	Enamelled cavity	YES
Bottom heating element1100 WGrill heating element2000 WConvection heating element2000 WConvection motor33 WCooling fan23 WOven lamp25 WMax. power3000 WFixation kitScrewsForced cooling system and smoke ventilationYESSTANDARD ACCESSORIESShelf rack1 (Put into cavity)Baking pan (enameled)1 (Put into cavity)Indicator1 (In control panel)Telescopic runner1 (Put into cavity)	Bottom element	Concealed
Grill heating element2000 WConvection heating element2000 WConvection motor33 WCooling fan23 WOven lamp25 WMax. power3000 WFixation kitScrewsForced cooling system and smoke ventilationYESSTANDARD ACCESSORIESShelf rack1 (Put into cavity)Baking pan (enameled)1 (Put into cavity)Indicator1 (In control panel)Telescopic runner1 (Put into cavity)	Top heating element	950 W
Convection heating element 2000 W  Convection motor 33 W  Cooling fan 23 W  Oven lamp 25 W  Max. power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1(Put into cavity)  Baking pan (enameled) 1(Put into cavity)  Indicator 1(In control panel)  Telescopic runner 1(Put into cavity)	Bottom heating element	1100 W
Convection motor33 WCooling fan23 WOven lamp25 WMax. power3000 WFixation kitScrewsForced cooling system and smoke ventilationYESSTANDARD ACCESSORIESShelf rack1 (Put into cavity)Baking pan (enameled)1 (Put into cavity)Indicator1 (In control panel)Telescopic runner1 (Put into cavity)	Grill heating element	2000 W
Cooling fan23 WOven lamp25 WMax. power3000 WFixation kitScrewsForced cooling system and smoke ventilationYESSTANDARD ACCESSORIESShelf rack1 (Put into cavity)Baking pan (enameled)1 (Put into cavity)Indicator1 (In control panel)Telescopic runner1 (Put into cavity)	Convection heating element	2000 W
Oven lamp 25 W  Max. power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1 (Put into cavity)  Baking pan (enameled) 1 (Put into cavity)  Indicator 1 (In control panel)  Telescopic runner 1 (Put into cavity)	Convection motor	33 W
Max. power 3000 W  Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1 (Put into cavity)  Baking pan (enameled) 1 (Put into cavity)  Indicator 1 (In control panel)  Telescopic runner 1 (Put into cavity)	Cooling fan	23 W
Fixation kit Screws  Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1(Put into cavity)  Baking pan (enameled) 1(Put into cavity)  Indicator 1(In control panel)  Telescopic runner 1(Put into cavity)	Oven lamp	25 W
Forced cooling system and smoke ventilation YES  STANDARD ACCESSORIES  Shelf rack 1 (Put into cavity)  Baking pan (enameled) 1 (Put into cavity)  Indicator 1 (In control panel)  Telescopic runner 1 (Put into cavity)	Max. power	3000 W
STANDARD ACCESSORIES  Shelf rack 1 (Put into cavity)  Baking pan (enameled) 1 (Put into cavity)  Indicator 1 (In control panel)  Telescopic runner 1 (Put into cavity)	Fixation kit	Screws
Shelf rack 1 (Put into cavity) Baking pan (enameled) 1 (Put into cavity) Indicator 1 (In control panel) Telescopic runner 1 (Put into cavity)	Forced cooling system and smoke ventilation	YES
Baking pan (enameled) 1 (Put into cavity) Indicator 1 (In control panel) Telescopic runner 1 (Put into cavity)		
Indicator 1 (In control panel) Telescopic runner 1 (Put into cavity)		1(Put into cavity)
Telescopic runner 1 (Put into cavity)	Baking pan (enameled)	<del>-</del>
	Indicator	
Power cord without plug 1(Put into cavity)	Telescopic runner	
	Power cord without plug	1(Put into cavity)