

## TESLA TA27FFCL-0932IAW



### FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WIFI, I FEEL

<b>Capacity</b>			9000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	2600(600-3200)      2900(600-3500)	
<b>Power input</b>		W	750(100-1100)      855(100-1100)	
<b>Current input</b>		A	3.6(0.6-5.0)      4.1(0.6-5.0)	
<b>SEER-SCOP/ Energy Class</b>		W/W	6,42/A++      4,11/A+	
<b>Operating range</b>		(°C)	16~49°C      -15~30°C	
<b>Energy consumption (per year, based on standard test results)</b>		kwh	142      817	
<b>Dehumidifying</b>		Kg/h	0.6	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX0/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I	
<b>Max. input consumption</b>		W	1700	
<b>Max. current</b>		A	8.0	
<b>Compressor</b>		Model	GSD088RKA6JV6B	
		Type	DC	
		Brand	Highly	
<b>Indoor</b>	<b>Fan motor</b>	Model	YYK18-4B	
		Power input	W	/
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1130/1015/900
	Indoor fan	Dia. / Length	mm	φ97.8x558
	Indoor Air Circulation		m³/h	560
	Indoor Noise Level dB		dB(A)	44/39/35/31/26
	Net Dimension (LxWxH)		mm	750X285X200
	Packing Dimension (LxWxH)		mm	820X347X277
	Net Weight/Gross Weight		Kg	7.5/9.7
<b>Outdoor</b>	<b>Fan motor</b>	Model	D-24-8	
		Power input	W	/
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	820
	Outdoor fan	Length	mm	390
	Outdoor Noise Level dB		dB(A)	61
	Net Dimension (LxWxH)		mm	730X545X285
	Packing Dimension (LxWxH)		mm	850X620X370
	Net Weight/Gross Weight		Kg	25/28
	Refrigerant type/weight		g	R32/530
Max. Discharge/Max. Suction pressure		Mpa	4.3/2.5	
<b>Refrigerant piping</b>	Liquid side / Gas side		mm	φ6,35 / φ9,52
	Max. refrigerant pipe length / Max. difference in level		m	20/10