

TESLA TA36FFCL-1232IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WIFI, I FEEL

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3500(800-3800) 3600(800-4100)	
Power input		W	1190(100-1500) 1150(100-1400)	
Current input		A	5.5(0.6-6.7) 5.4(0.6-6.4)	
SEER-SCOP/ Energy Class		W/W	6,21/A++ 4,04/A+	
Operating range		(°C)	16~49°C -15~30°C	
Energy consumption (per year, based on standard test results)		kwh	198 902	
Dehumidifying		Kg/h	0.8	
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1900	
Max. current		A	9.5	
Compressor		Model	GSD088RKA6JV6B	
		Type	DC	
		Brand	Highly	
Indoor	Fan motor	Model	YYK18-4B	
		Power input	W	/
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1130/1015/900
	Indoor fan	Dia. / Length	mm	φ97.8x558
	Indoor Air Circulation		m³/h	560
	Indoor Noise Level dB		dB(A)	43/39/36/32/27
	Net Dimension (LxWxH)		mm	750x285x200
	Packing Dimension (LxWxH)		mm	820X347X277
	Net Weight/Gross Weight		Kg	8.0/10.0
Outdoor	Fan motor	Model	D-24-8	
		Power input	W	31
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	860
	Outdoor fan	Length	mm	390
	Outdoor Noise Level dB		dB(A)	62
	Net Dimension (LxWxH)		mm	730x545x285
	Packing Dimension (LxWxH)		mm	850X620X370
	Net Weight/Gross Weight		Kg	25/28
	Refrigerant type/weight		g	R32/600
Max. Discharge/Max. Suction pressure		Mpa	4.3/2.5	
Refrigerant piping	Liquid side / Gas side		mm	φ6,35 / φ9,52
	Max. refrigerant pipe length / Max. difference in level		m	20/10