

TESLA TA36FFLL-12410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer filter, I FEEL

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling	Heating
Rated capacity		W	3300	3450
Power input		W	1028	955
Current input		A	4.47	4.15
EER-COP		W	3.21	3.61
Energy Class			A	A
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1700	
Max. current		A	8.5	
Compressor		Model	ASM125V1VFT	
		Type	ROTARY	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK18-4B	
		Power input	W	18
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1330
	Indoor fan	Dia. / Length	mm	φ97.8*558
	Indoor Air Circulation		m³/h	560
	Indoor Noise Level dB		dB(A)	36/33/30/27
	Net Dimension (L×W×H)		mm	800x300x197
	Packing Dimension (L×W×H)		mm	870x370x282
	Net Weight/Gross Weight		Kg	43/687
	Outdoor	Fan motor	Model	YDK25-6
Power input			W	25
Capacity			uF	1.5
Outdoor Fan Speed RPM			r/min	820
Outdoor fan		Length	mm	φ390*140
Outdoor Noise Level dB		dB(A)	52	
Net Dimension (L×W×H)		mm	660x500x240	
Packing Dimension (L×W×H)		mm	780x570x345	
Net Weight/Gross Weight		Kg	29/34	
Refrigerant type/weight		g	R410/660	
Max. Discharge/Max. Suction pressure		Mpa	4.15/1.15	
Refrigerant piping		Liquid side / Gas side	mm	φ6.35(0,5) /φ9.52(0,6)
		Max. refrigerant pipe length / Max. difference in level	m	18/6
Operation Temperature Range		Cooling	(min - max) °C	14~43 °C
		Heating		-7~30 °C