

TESLA TA53FFCL-1832IA



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), I FEEL

Capacity			18000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	5000(1500-5200) 5280(130-5400)	
Power input		W	1500(130-1550) 1450(220-1450)	
Current input		A	6.6(0.9-6.8) 6.4(1.4-6.5)	
SEER-SCOP/ Energy Class		W/W	6,44/A++ 4,08A+	
Operating range		(°C)	16~49°C -15~30°C	
Energy consumption (per year, based on standard test results)		kwh	272 1236	
Dehumidifying		Kg/h	1.6	
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1500	
Max. current		A	6.6	
Compressor		Model	KSN102D32UFZA	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK25-4D	
		Power input	W	66
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	1080/965/850
	Indoor fan	Dia. / Length	mm	φ107.9/661
	Indoor Air Circulation		m³/h	850
	Indoor Noise Level dB		dB(A)	57/46/42/39/35/25
	Net Dimension (L×W×H)		mm	900×310×225
	Packing Dimension (L×W×H)		mm	970×382×302
	Net Weight/Gross Weight		Kg	11/13
Outdoor	Fan motor	Model	D-40-8	
		Power input	W	62
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	900
	Outdoor fan	Length	mm	421
	Outdoor Noise Level dB		dB(A)	62
	Net Dimension (L×W×H)		mm	800×545×315
	Packing Dimension (L×W×H)		mm	920×620×400
	Net Weight/Gross Weight		Kg	30.5/33.5
	Refrigerant type/weight		g	R32/970
Max. Discharge/Max. Suction pressure		Mpa	4.3/2.5	
Refrigerant piping	Liquid side / Gas side		mm	φ6,35 / φ12,7
	Max. refrigerant pipe length / Max. difference in level		m	20/10