

TESLA TA71FFUL-2432IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Top plate/cover improved, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), WIFI, I FEEL

Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	7000(1500-7200) 7100(800-7800)	
Power input		W	1800(200-1950) 1850(300-2200)	
Current input		A	8(0.9-8.5) 8.1(1.3-9.8)	
SEER-SCOP/ Energy Class		W/W	6,2/A++ 4,01/A+	
Operating range		(°C)	16~49°C -15~30°C	
Energy consumption (per year, based on standard test results)		kwh	356 1606	
Dehumidifying		Kg/h	3	
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1800	
Max. current		A	8	
Compressor		Model	KTN150D30UFZ	
		Type	DC	
		Brand	GMCC	
Indoor	Fan motor	Model	D-65-8	
		Power input	W	72
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	1080/965/850
	Indoor fan	Dia. / Length	mm	φ107.9*839
	Indoor Air Circulation		m³/h	1250
	Indoor Noise Level dB		dB(A)	62/47/43/40/36/26
	Net Dimension (L×W×H)		mm	1082×330×233
	Packing Dimension (L×W×H)		mm	1155×397×312
	Net Weight/Gross Weight		Kg	14/16
Outdoor	Fan motor	Model	D-65-8	
		Power input	W	65
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	880
	Outdoor fan	Length	mm	470
	Outdoor Noise Level dB		dB(A)	66
	Net Dimension (L×W×H)		mm	825×655×310
	Packing Dimension (L×W×H)		mm	945×725×435
	Net Weight/Gross Weight		Kg	40/42
	Refrigerant type/weight		g	R32/1300
Max. Discharge/Max. Suction pressure		Mpa	4.3/2.5	
Refrigerant piping	Liquid side / Gas side		mm	φ6,35/φ15,88
	Max. refrigerant pipe length / Max. difference in level		m	25/15