

TESLA TC35P4-1232IAW



FEATURES

I feel, Self-cleaning, Celsius & Fahrenheit switch, Turbo mode, Timer, Sleep mode, ECO mode, Low battery indication, Digital display lamplight, Button lock, Auto restart, Auto mode, Vertical swing, Horizontal swing, Auto fan mod, Digital display, Self diagnosis, Technician test mode, Silent mode, Do not disturb, Rapid cooling & rapid heating, Refrigerant leakage detection, Smart air supply, Alarm output, Louver position memory, Emergency button, Anti-cold wind, Low voltage operation, 5 grades outdoor fan speed, Remote ON/OFF, Fireproof E-box, WIFI control, Drainage pipe, 3D air flow, 4D air flow, Multiflow 360°, Heating at -15°C, Cooling at -15°C, Low ambient cooling Kit, Stop valve cover, Dual drainage

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3500(1000~3700) 3660(1000~3800)	
Power input		W	1050(280~1500) 950(290~1750)	
Current input		A	5.8(1.5~9.0) 4.7(1.5~10.0)	
SEER-SCOP/ Energy Class		W/W	6,1/ A++ 4,0/A+	
Operating range		(°C)	-15°C - 55°C -15°C - 30°C	
Energy consumption (per year, based on standard test results)		kwh	200 855	
Dehumidifying		Kg/h	1.2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1480	
Max. current		A	9	
Compressor		Model	KSN98D22UFZ	
		Type	Rotary	
		Brand	GMCC	
Indoor	Fan motor	Model	YDK-13G-4P3	
		Power input	W 13W output	
		Capacity	uF 1.5	
		Indoor Fan Speed RPM	r/min 800/1100/1220/1250	
	Indoor fan	Dia. / Length	mm φ7	
	Indoor Air Circulation		m³/h	550
	Indoor Noise Level dB		dB(A)	50/40/39/32/22/19
	Net Dimension (L×W×H)		mm	864x300x200
	Packing Dimension (L×W×H)		mm	950x380x290
	Net Weight/Gross Weight		Kg	9.5/12.5
Outdoor	Fan motor	Model	DRN-310-34-8-1	
		Power input	W 34W output	
		Capacity	uF /	
		Outdoor Fan Speed RPM	r/min 850	
	Outdoor fan	Length	mm 755	
	Outdoor Noise Level dB		dB(A)	60
	Net Dimension (L×W×H)		mm	805x495x305
	Packing Dimension (L×W×H)		mm	850x550x350
	Net Weight/Gross Weight		Kg	25/28
	Refrigerant type/weight		g	R32/750g
Max. Discharge/Max. Suction pressure		Mpa	4,3/1.5	
Refrigerant piping	Liquid side / Gas side	mm	φ6.35/φ9.52	
	Max. refrigerant pipe length / Max. difference in level	m	25/10	