



Features

High-density filter, Self-cleaning, Low ambient kit (function), 4 indoor fan speeds, 5 outdoor unit fan motor speeds, Special coating on the evaporator, Refrigerant leakage detection, Turbo operation, Emergency use (when the temperature sensor is abnormal), Sleep mode, 1W in standby mode, 2 connection methods, Automatic restart, Timer, H-shaped installation plate, Air vent position memory, Intelligent switch, Breeze.

Capacity		12000BTU	
Rated volt and frequency		220-240V~/50HZ	
Mode	V/Hz	Cooling	Heating
Rated capacity		12000(3800~13400)	10000(2800~11500)
Power input	W	1320(83~1600)	1190(167~1400)
Current input	W	5.8(0.8~7.3)	5.3(1.4~6.4)
SEER-/ Energy Class	A	6,5/A++	/
SCOP/ Energy Class - average		/	4,1/A+
SCOP/ Energy Class - warmer		/	5,2/A+++
Operating range		15-50	-20-30
Energy consumption (per year, based on standard test results)	°C	188	/
Energy consumption (per year, based on standard test results) - average	kWh	/	957
Energy consumption (per year, based on standard test results) - warmer	kWh	/	823
Dehumidifying	Kg/h	1,7	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	2150	
Max. current	A	10	
Compressor	Model	KSK103D32UEZ31	
	Type	Rotary	
	Brand	GMCC	
Indoor	Indoor Air Circulation	m ³ /h	530
	Indoor Noise Level dB	dB(A)	39.5/35.5/25/21.5
	Net Dimension	mm	805x194x285
	Packing Dimension	mm	870x270x365
	Net Weight/Gross Weight	Kg	7.3/9.5
Outdoor	Outdoor Noise Level dB	dB(A)	64
	Net Dimension	mm	720x270x495
	Packing Dimension	mm	835x300x540
	Net Weight/Gross Weight	Kg	21/22.8
	Refrigerant type		R32
	Refrigerant weight	Kg	0,52
	GWP		675
	tCO ₂ eq.		0,35
Max. Discharge/Max. Suction pressure	Mpa	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side/Length	mm	Dg4/Dg8 (1/4-3/8)
	Max. refrigerant pipe length/ Max. difference in level	m	25/10