

TESLA TM36AF21-1232IAW



FEATURES

High density filter, Cold-catalyst filter, Self-cleaning, Low ambient kit (function), Five speed outdoor fan motor, Golden fin, Refrigerant leakage detect, Turbo operation, Horizontal louver autoswing, Emergency Using (when temp sensor is abnormal), Sleep mode, 1W standby, 2 ways piping connection, Auto-restart, Timer, H-shaped installation plate, Louver position memory function, Mono & multi compatible, I Remote (Engineering Mode), Intelligent dusting switch, Breeze away, WIFI

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling
Rated capacity		W	3510(1110~4160)
Power input		W	1213(130~1580)
Current input		A	5.27(0.5~6.9)
SEER-SCOP/ Energy Class		W/W	6,1/ A++
Operating range		(°C)	-15°C - 50°C
Energy consumption (per year, based on standard test results)		kwh	221
Dehumidifying		Kg/h	1.2
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2150
Max. current		A	10
Compressor	Model		KSK103D33UEZ3(YJ)
	Type		Rotary
	Brand		GMCC
Indoor	Fan motor	Model	YKFG-13-4-38L-4
		Power input	W
		Capacity	uF
		Indoor Fan Speed RPM	r/min
	Indoor fan	Dia. / Length	mm
	Indoor Air Circulation		m³/h
	Indoor Noise Level dB		dB(A)
	Net Dimension (L×W×H)		mm
	Packing Dimension (L×W×H)		mm
	Net Weight/Gross Weight		Kg
Outdoor	Fan motor	Model	ZKFN-34-10-1
		Power input	W
		Capacity	uF
		Outdoor Fan Speed RPM	r/min
	Outdoor fan	Length	mm
	Outdoor Noise Level dB		dB(A)
	Net Dimension (L×W×H)		mm
	Packing Dimension (L×W×H)		mm
	Net Weight/Gross Weight		Kg
	Refrigerant type/weight		g
Refrigerant piping	Max. Discharge/Max. Suction pressure		Mpa
	Liquid side / Gas side		mm
	Max. refrigerant pipe length / Max. difference in level		m