



Features

High-density filter, Self-cleaning, Low ambient kit (function), 4 indoor fan speeds, 5 outdoor unit fan motor speeds, Special coating on the evaporator, Refrigerant leakage detection, Turbo operation, Emergency use (when the temperature sensor is abnormal), Sleep mode, 1W in standby mode, 2 connection methods, Automatic restart, Timer, H-shaped installation plate, Air vent position memory, Intelligent switch, Breeze, Horizontal air deflector, Wi-Fi

Capacity		18000BTU	
Rated volt and frequency		220-240V~/50HZ	
Mode	V/Hz	Cooling	Heating
Rated capacity		18000(6200~21000)	19000(4400~23000)
Power input	W	1550(140~2300)	1570(220~2350)
Current input	W	6.7(0.6~10)	6.8(0.95~10.2)
SEER-/ Energy Class	A	7,4/A++	/
SCOP/ Energy Class - average		/	4,0/A+
SCOP/ Energy Class - warmer		/	5,1/A+++
Operating range		15-50	-20-30
Energy consumption (per year, based on standard test results)	°C	247	/
Energy consumption (per year, based on standard test results) - average	kWh	/	1435
Energy consumption (per year, based on standard test results) - warmer	kWh	/	1208
Dehumidifying	Kg/h	2,5	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	2500	
Max. current	A	13	
Compressor	Model	KSN140D21UFZ	
	Type	Rotary	
	Brand	GMCC	
Indoor	Indoor Air Circulation	m ³ /h	840
	Indoor Noise Level dB	dB(A)	42.5/36/26/20
	Net Dimension	mm	957x213x302
	Packing Dimension	mm	1035x295x385
	Net Weight/Gross Weight	Kg	10/13
Outdoor	Outdoor Noise Level dB	dB(A)	63
	Net Dimension	mm	805x330x554
	Packing Dimension	mm	915x370x615
	Net Weight/Gross Weight	Kg	32.7/35.4
	Refrigerant type		R32
	Refrigerant weight	Kg	1,08
	GWP		675
	tCO ₂ eq.		0,72
Max. Discharge/Max. Suction pressure	Mpa	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side/Length	mm	Dg4/Dg8 (1/4-1/2)
	Max. refrigerant pipe length/ Max. difference in level	m	30/20