



Features

High-density filter, Self-cleaning, Low ambient kit (function), 4 indoor fan speeds, 5 outdoor unit fan motor speeds, Special coating on the evaporator, Refrigerant leakage detection, Turbo operation, Emergency use (when the temperature sensor is abnormal), Sleep mode, 1W in standby mode, 2 connection methods, Automatic restart, Timer, H-shaped installation plate, Air vent position memory, Intelligent switch, Breeze, Horizontal air deflector, Wi-Fi

Capacity		24000BTU	
Rated volt and frequency		220-240V~/50HZ	
Mode	V/Hz	Cooling	Heating
Rated capacity		24000(7100~27000)	25000(5500~27000)
Power input	W	2600(420~3150)	2400(300~2750)
Current input	W	11.5(1.8~13.8)	11(1.3~12.2)
SEER-/ Energy Class	A	6,1/A++	/
SCOP/ Energy Class - average		/	4,0/A+
SCOP/ Energy Class - warmer		/	5,1/A+++
Operating range		15-50	-20-30
Energy consumption (per year, based on standard test results)	°C	405	/
Energy consumption (per year, based on standard test results) - average	kWh	/	1680
Energy consumption (per year, based on standard test results) - warmer	kWh	/	1537
Dehumidifying	Kg/h	3,1	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	3500	
Max. current	A	13,5	
Compressor	Model	KTM240D43UKT	
	Type	Rotary	
	Brand	GMCC	
Indoor	Indoor Air Circulation	m³/h	980
	Indoor Noise Level dB	dB(A)	45/40.5/36/29.5
	Net Dimension	mm	1040x220x327
	Packing Dimension	mm	1120x405x315
	Net Weight/Gross Weight	Kg	12.3/15.8
Outdoor	Outdoor Noise Level dB	dB(A)	67
	Net Dimension	mm	890x342x673
	Packing Dimension	mm	995x398x740
	Net Weight/Gross Weight	Kg	42.9/45.9
	Refrigerant type		R32
	Refrigerant weight	Kg	1.42
	GWP		675
	tCO ₂ eq.		0,95
	Max. Discharge/Max. Suction pressure	Mpa	4.3/1.7
Refrigerant piping	Liquid side/ Gas side/Length	mm	Dg4/Dg8 (3/8-5/8)
	Max. refrigerant pipe length/ Max. difference in level	m	50/25